

Food and General Services

Power Connections

Large equipment like back-up generators, compactors, loading dock equipment, HVAC units and air handlers all need high-capacity, safe and reliable power. These enclosures are non-metallic Type 4X Rated for washdown.



Circuit-Lock®

Unfused Disconnect Switches

Description	Catalog No.
30A disconnect switch	HBLDS3*
60A disconnect switch	HBLDS6*
100A disconnect switch	HBLDS10*
Auxiliary contacts, "break after main break" 1 set of n/o & n/c contacts	HBLAC1
Auxiliary contacts, "break before main break" 1 set of n/o contacts	HBLAC2

*Add suffix "AC" for disconnect with one HBLAC1 aux. contact.



Circuit-Lock®

Fused Disconnect Switches

Description	Catalog No.
30A disconnect switch	FDS30*
60A disconnect switch	FDS60*
Auxiliary contacts, normally open, A600 pilot duty	ACFSNO
Auxiliary contacts, normally closed, A600 pilot duty	ACFSNC

*Class "J" fuses not included.

30A Units supplied with (2) 1 in. N.P.T. raintight conduit fittings.

60A Units supplied with (2) 1 1/4 in. N.P.T. raintight conduit fittings.

Power and Multimedia Delivery

Hubbell's HI-Impact enclosures are available in NEMA 3R, 4, 4X, 12 and 13 ratings, providing a mini telecom room for harsh environments.

User-Configurable Version

Description	Height		
	24" (610)	36" (914.4)	48" (1219.2)
Cold Rolled Steel, Gray Powder Coat, NEMA 3R	IR2U3RG	IR3U3RG	—
Cold Rolled Steel, Gray Powder Coat, NEMA 4/12/13	IR2UG	IR3UG	IR4UG
Stainless Steel, Brushed, Unpainted, NEMA 4X	IR2USS	IR3USS	—

Pre-Configured Version

Description	Height	
	36" (914.4)	48" (1219.2)
Cold Rolled Steel, Gray Powder Coat, NEMA 4/12/13	IR3PG	IR4PG
Contents: 1 enclosure; 1 bottom-hinged patch panel bracket, 4U (REK19); and 1 equipment mounting bracket, 5U (REKZ).		



Power Connections

Watertight Safety-Shroud® Twist-Lock® devices are constructed of highly impact-resistant thermoplastic for a UL Type 4X rating in heavy duty environments. The integral Safety-Shroud virtually eliminates bent and broken plug blades, leading to longer equipment life while providing extra protection for personnel.

Watertight Safety-Shroud® Twist-Lock®

NEMA Rating	Color	Coded by Voltage	Poles/Wires	Plug	Connector	Receptacles
20A	125V	L5-20	2P/3W	HBL2311SW	HBL2313SW	HBL2310SW
20A	250V	L6-20	2P/3W	HBL2321SW	HBL2323SW	HBL2320SW
20A	277V AC	L7-20	2P/3W	HBL2331SW	HBL2333SW	HBL2330SW
20A	3Ø 250V	L15-20	3P/4W	HBL2421SW	HBL2423SW	HBL2420SW
30A	3Ø 250V AC	L15-30	3P/4W	HBL2721SW	HBL2723SW	HBL2720SW
30A	3Ø 480V AC	L16-30	3P/4W	HBL2731SW	HBL2733SW	HBL2730SW



Additional Products of Interest



Watertight Devices

When it comes to safety, most everyone knows that water and electricity can create a dangerous environment. Ensuring a watertight seal for electrical devices is critical to ensuring maximum safety of personnel in any wet environment. Hubbell Watertight Twist-Lock® devices have become the industry standard for maintaining a watertight seal.



HI-Impact™ Copper Connectors

HI-Impact connectors provide a rugged, durable IP67 Rated connection in a standard configuration for Hubbell Category 6 and 5e rated connectivity.



Stainless Steel Data Plates

Stainless steel plates are designed for flush mounting of Hubbell connectivity providing corrosion resistance from frequent washdown.