



Straight Blade Devices

15 and 20 Ampere, 125 Volts

2 Pole, 3 Wire Grounding

Hospital Grade – Plugs and Connector Bodies**HBL8215C****HBL8215CAT****HBL8115V****HBL8219C****HBL8219CT****HBL8119V****IP20**
SUITABILITY**15A 125V**
NEMA 5-15P
UL CSA**20A 125V**
NEMA 5-20P
UL CSA**Hospital Grade ● Plugs****Insulgrip®**

Description	Cord Diameter	Catalog Numbers	
Black and white nylon.	.230"-.720" (5.8-18.3)	HBL8215C	HBL8315C
Transparent housing.	.230"-.720" (5.8-18.3)	HBL8215CT	HBL8315CT
8 position angle plug, transparent housing.	.250"-.655" (6.4-16.6)	HBL8215CAT*	HBL8315CAT*

Valise®

Description	Cord Diameter	Catalog Numbers	
White nylon.	.300"-.660" (7.6-16.8)	HBL8115V	HBL8364V
Insulation displacement, white nylon.	.300"-.360" (7.6-9.1)	HBL8013V*	—

Notes: *Not Fed. Spec. Listed.

See page A-45 for accessories.

IP20
SUITABILITY**15A 125V**
NEMA 5-15R
UL CSA
0.5 HP**20A 125V**
NEMA 5-20R
UL CSA
1 HP**Hospital Grade ● Connector Bodies****Insulgrip®**

Description	Cord Diameter	Catalog Numbers	
Black and white nylon.	.230"-.720" (5.8-18.3)	HBL8219C	HBL8319C
Transparent housing.	.230"-.720" (5.8-18.3)	HBL8219CT	HBL8319CT

Note: See page A-45 for accessories.


Valise®

Description	Cord Diameter	Catalog Numbers	
White nylon.	.300"-.660" (7.6-16.8)	HBL8119V	—

Hospital Products

15 and 20 Ampere, 125 Volts

2 Pole, 3 Wire Grounding

Hospital Grade – Plugs and Connector Bodies
IP20
SUITABILITY
**Hospital Grade ● Plugs****Insulgrip®**

Description	Cord Diameter	Catalog Numbers	
Black and white nylon.	.230"-.720" (5.8-18.3)	HBL8215C	HBL8315C
Transparent housing.	.230"-.720" (5.8-18.3)	HBL8215CT	HBL8315CT
8-position angle plug, transparent housing.	.250"-.655" (6.4-16.6)	HBL8215CAT*	HBL8315CAT*

Valise®

Description	Cord Diameter	Catalog Numbers	
White nylon.	.300"-.660" (7.6-16.8)	HBL8115V	HBL8364V
Insulation displacement, white nylon.	.300"-.360" (7.6-9.1)	HBL8013V*	—

Note: *Not Fed. Spec. Listed.


IP20
SUITABILITY
**Hospital Grade ● Connector Bodies****Insulgrip®**

Description	Cord Diameter	Catalog Numbers	
Black and white nylon.	.230"-.720" (5.8-18.3)	HBL8219C	HBL8319C
Transparent housing.	.230"-.720" (5.8-18.3)	HBL8219CT	HBL8319CT

Valise®

Description	Cord Diameter	Catalog Numbers	
White nylon.	.300"-.660" (7.6-16.8)	HBL8119V	—



Hospital Products

Technical Information



HBL8115V



HBL8119V

Hospital Grade Valise® Plugs and Connectors

Specifications

Plug	Part	Description
Typical Specification—Catalog No. HBL8115V.	Plug	15A
Manufacturer's Identification—Hubbell HBL8115V Plug.	Housing	Nylon
Description—Hospital Grade Straight Body Plug.	Blades	Brass
Type— 2 Pole, 3 Wire, Grounding.	Ground Blade	Brass
Rating—15A, 125V.	Terminal Screws	Multiple Drive
Certifications—UL Listed to UL498.	Cable Inserts	Polyphenylene Oxide
File E1706, CSA Certified to C22.2	Terminal Clamps	Plated CR Steel
No. 42 File LR280. Fed. Spec. W-C 596.	Body Holding Screws	Multiple Drive
IP Suitability—IP20.		
Connector		
Typical Specification—Catalog No. HBL8119V.	Connector	15A
Manufacturer's Identifications—Hubbell HBL8119V.	Housing	Nylon
Connector Body.	Contact and Ground Spring	Brass
Description—Hospital Grade Straight Connector Body.	Terminal Screws	Multiple Drive
Type—2 Pole, 3 Wire, Grounding.	Cable Inserts	Polyphenylene Oxide
Rating—15A, 125V.	Terminal Clamps	Plated CR Steel
Certifications—UL Listed to UL498.	Body Holding Screws	Multiple Drive
File E1706, CSA Certified to C22.2		
No. 42 File LR280. Fed. Spec. W-C 596.		
IP Suitability—IP20.		

Performance

Electrical	
Dielectric Voltage	Withstands 2000V AC minimum.
Max. Working Voltage	125V or 250V as rated.
Current Interrupting	Certified for current Interrupting at full rated current.
Temperature Rise	Max. 30°C temperature rise at full rated current.
Mechanical	
Terminal Identification	Terminals identified in accordance with UL and CSA (Brass, White, & Green)
Terminal Accomodation	#16 to #12 AWG.
Product Identification	Ratings are a permanent part of the device.
Torque	Terminal screws 12 in.-lbs. Cord clamp screws 7 to 10 in.-lbs.
Cord Diameter Range	.300" to .660" (7.6 to 16.8)
Enviromental-Material	
Flammability	UL 94 HB
Operating Temperature	Maximum continuous 75°C, minimum -40°C (w/o impact).
Standards	
NEMA Configurations WD6.	
Listed to UL Standard UL498 and UL Verified to Ped. Spec. W-C 596.	
Certified to CSA Standard C22.2 No. 42.	