



2X2 Flush FRPT 3" Diameter – One Piece Units

Catalog Number

PT2X2BL	Black	2X2 Aluminum Poke-Through
PT2X2GY	Gray	
PT2X2IGBL*	Black	
PT2X2IGGY*	Gray	

* Includes pre-wired 20A isolated ground duplex Style Line receptacle.

Complete assembled unit

- PT2X2FIT through-floor fitting.
- Pre-wired 20A duplex Style Line® receptacle & (2) Category 5e data jacks.
- Non-metallic cover.
- Painted aluminum flange.



Catalog Number

PT2X2BRS3	Black/Brass	2X2 Brass Poke-Through
PT2X2BRS	Brass Finish/Brass	
PT2X2IGBRS3*	Black/Brass	
PT2X2IGBRS*	Brass Finish/Brass	

* Includes pre-wired 20A isolated ground duplex Style Line receptacle.

Complete assembled unit

- PT2X2FIT through-floor fitting.
- Pre-wired 20A duplex Style Line receptacle & (2) Category 5e data jacks.
- Non-metallic cover.
- Solid brass flange.



2X2 Flush FRPT 3" Diameter – Two Piece Units

Through-Floor Fitting

Catalog Number

PT2X2FIT

Multi-Channel Through-Floor Fitting

Through-floor fitting with (1) 3/4" trade size conduit stem with junction box for power and (2) 1/2" low voltage conduit entrances.



Specifications:

- UL Listed and CSA Certified.
- 1- 4 hour fire rating (1-3 hour for steel floor units and concrete topping (D900 Series Design)).
- For 2 1/4" to 7" floor thickness.
- UL installation spacing. Minimum 2 ft. on center and not more than one per 65 sq. ft. of floor area.

Service Fittings

Catalog Number

PT2X2SFBL	Black	2X2 Aluminum Service Fitting
PT2X2SFGY	Gray	

- Pre-wired 20A duplex Style Line receptacle & (2) Category 5e data jacks.
- Non-metallic cover.
- Painted aluminum flange.



Catalog Number

PT2X2SFBR3	Black/Brass	2X2 Brass Service Fitting
PT2X2SFBR	Brass Finish/Brass	

- Pre-wired 20A duplex Style Line receptacle & (2) Category 5e data jacks.
- Non-metallic cover.
- Solid brass flange.



Accessories

Catalog Number

PT2X2CBL	Black	Non-Metallic Replacement Covers
PT2X2CGY	Gray	
PT2X2CBRS	Brass Finish	

