



2X2 Flush FRPT 3" Diameter – One Piece Units

Catalog Number			Catalog Number		
PT2X2BL	Black	2X2 Aluminum Poke-Through 	PT2X2BRS3	Black/Brass	2X2 Brass Poke-Through 
PT2X2GY	Gray		PT2X2BRS	Brass Finish/Brass	
PT2X2IGBL*	Black		PT2X2IGBRS3*	Black/Brass	
PT2X2IGGY*	Gray		PT2X2IGBRS*	Brass Finish/Brass	
* Includes pre-wired 20A isolated ground duplex Style Line receptacle.			* Includes pre-wired 20A isolated ground duplex Style Line receptacle.		
Complete assembled unit ■ PT2X2FIT through-floor fitting. ■ Pre-wired 20A duplex Style Line® receptacle & (2) Category 5e data jacks. ■ Non-metallic cover. ■ Painted aluminum flange.			Complete assembled unit ■ PT2X2FIT through-floor fitting. ■ Pre-wired 20A duplex Style Line receptacle & (2) Category 5e data jacks. ■ Non-metallic cover. ■ Solid brass flange.		

2X2 Flush FRPT 3" Diameter – Two Piece Units

Through-Floor Fitting

Through-Floor Fitting		Catalog Number	
PT2X2FIT		Multi-Channel Through-Floor Fitting	
Through-floor fitting with (1) ¾" trade size conduit stem with junction box for power and (2) ½" low voltage conduit entrances.			Specifications:
			■ UL Listed and CSA Certified. ■ 1- 4 hour fire rating (1-3 hour for steel floor units and concrete topping (D900 Series Design)). ■ For 2 ¼" to 7" floor thickness. ■ UL installation spacing. Minimum 2 ft. on center and not more than one per 65 sq. ft. of floor area.

Service Fittings

Catalog Number			Catalog Number		
PT2X2SFBL	Black	2X2 Aluminum Service Fitting	PT2X2SFBR3	Black/Brass	2X2 Brass Service Fitting
PT2X2SFGY	Gray		PT2X2SFBR	Brass Finish/Brass	
■ Pre-wired 20A duplex Style Line receptacle & (2) Category 5e data jacks. ■ Non-metallic cover. ■ Painted aluminum flange.			■ Pre-wired 20A duplex Style Line receptacle & (2) Category 5e data jacks. ■ Non-metallic cover. ■ Solid brass flange.		

Accessories

Catalog Number			
PT2X2CBL	Black	Non-Metallic Replacement Covers 	
PT2X2CGY	Gray		
PT2X2CBRS	Brass Finish		