

Hubbell SystemOne Non-Metallic Floor Box









S1PFB Round Multi-Service PVC Floor Box Features (2) 1 1/2" hubs for low voltage and (2) 1" hubs for power. Includes concrete cover and a variety of reducers and closure plugs that allow a full range of conduit sizes.		Min. Depth of Pour Capacity Diameter (External) Diameter (Internal) Height Hubs Conduit Selection	Ranges from 3" to 5" depending on application. See sub-plates below for details. 100 cubic inches prior to cutting level to floor (19.5 cubic inches per inch of depth). 5.75" 5.00" 6.00" (2) 1 1/2" and (2) 1" conduit hubs Accepts 3/4", 1", 1 1/4", 1 1/2" schedule 40 and schedule 80 rigid PVC conduit and E.N.T. (electrical non-metallic tubing).
S1DIV1 Side by Side Divider Required for use with catalog number S1SP (Style Line®/GFCI) sub-plate when used in multi-service applications. All other sub-plates include the appropriate dividers.			

Hubbell SystemOne Universal Covers

Universal, Cast Aluminum Carpet Flange & Cover Assembly Catalog Number S1CFCBRS Brass S1CFCAL Aluminum S1CFCBL Black S1CFCGY Gray S1CFCI Ivory 	Universal, Cast Aluminum Tile Flange & Cover Assembly Catalog Number S1TFCBRS Brass S1TFCAL Aluminum S1TFCBL Black S1TFCGY Gray S1TFCI Ivory 
--	--

■ Cast aluminum construction
■ Powder coat finish

Sub-Plates

Catalog Number S1SP Style Line/GFCI (2) Style Line openings for power and/or datacom applications. 	Catalog Number S1SP4X4 Hubbell 4 X 4 (4) 20A, 125V receptacles. (4) Keystone openings for Hubbell jacks or flush A/V connectors. 	Catalog Number S1SPTL Twist-Lock® + Data 20 or 30 Amp TL rec. (1.56" OD). (2) Keystone openings for Hubbell jacks or flush A/V connectors. 
S1SP4IM Hubbell Datacom 1 unit flush INFIneSTATION™ opening. 3 unit recessed INFIneSTATION opening for data, voice, and A/V applications. (See back cover for details) 	S1SP3IM Hubbell A/V + Power (1) 20A, 125V receptacle. 3 unit recessed INFIneSTATION opening for data, voice, and A/V applications. (See back cover for details) 	S1SPFFBRS Brass Furniture S1SPFFAL Alum. Feed Cover/ S1SPFFBL Black Flange S1SPFFGY Gray (1) 3/4" & (1) 1 1/2" KOs for power and/or datacom applications. Universal Cover not required. Includes carpet flange. 
S1SPEXT1 Extron® MAAP + Power (1) 20A, 125V receptacle. Recessed opening for (3) single Extron MAAP Series adapter plates. 	S1SPEXT2 Extron AAP + Power (1) 20A, 125V receptacle. Recessed opening for (1) single Extron MAAP and (2) single AAP Series adapter plates. 	S1SPEXT3 Extron Datacom Recessed opening for (2) single Extron MAAP and (2) single AAP Series adapter plates. 
S1SPORT Ortronics Series II® + Power (1) 20A, 125V receptacle. Recessed opening for (3) 1 unit Ortronics Series II modules. 	S1SPTRAC Ortronics TracJack® + Power (1) 20A, 125V receptacle. Recessed bezel for (6) Ortronics TracJack modules. 	S1SPMAX Siemon MAX® + Power (1) 20A, 125V receptacle. Recessed bezel for (6) Siemon MAX modules. 
S1SP4X4PA Panduit Mini-Com® 4 X 4 (4) 20A, 125V receptacles (4) Openings for Panduit Mini-Com Connectivity. 	S1SP4X4SYS SYSTIMAX® 4 X 4 (4) 20A, 125V receptacles. (4) Openings for SYSTIMAX Connectivity. 	

○ Signifies minimum depth of concrete pour in inches for Hubbell SystemOne S1PFB Floor Box.