

90W48-S

Wetguard Watertight Straight Blade Outlet

20 Amp, 250 Volt, NEMA 6-20, 2P, 3W, Straight Blade Single Outlet, Industrial Grade, Grounding, Wetguard - YELLOW

ROHS Compliant : Yes

- **BATTLE THE ELEMENTS-** Resistant to water, acids, alkalies, and many automotive and industrial lubricants and solvents.
- **ADVANCED LID DESIGN-** Our spring-loaded flip lid is impact and chemical resistant with a Valox® PBT cover
- **MORE SECURE-** Dual-hasp provides additional lockout /tagout option for added security.
- **DURABLE-** Ideal for harsh environments with added resistance against heat, chemical corrosion, and physical abrasion

UPC Code : 078477519509

Country Of Origin : Mexico

NEMA :  6-20R

Technical Information

Electrical Specifications

Amperage : 20 A

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Grounding

Pole : 2

Temperature Rise : Max 30C
after 250 cycles OL at 200
percent rated current

Voltage : 250 VAC

Wire : 3

Environmental Specifications

Enclosure Rating : NEMA 4,
4X, 12 IEC IP66

Environment : Wet

Flammability : Rated V-2 per
UL 94 (wiring module)

Operating Temperature : -40°
C to 60°C

Material Specifications

**Blades/Contacts, Terminal
Clamps :** Electroless Nickel-
coated Brass

Cover Gasket : Santoprene
TPV

Cover/Lid : Valox PBT

Mounting and Assembly

Screws : Stainless steel, non-
magnetic

Terminal Screws : Electroless
Nickel-coated Brass

**Torsion Spring Mechanism
(Flip Lids) :** Stainless Steel

Mechanical Specifications

Product ID : Ratings and
NEMA I.D. permanently marked
on device

Terminal Accom. : #16 AWG
to #10 AWG

Wiring Module : Nylon

Wiring Module Mounting Cup
: Valox PBT

Product Features

Brand : Wetguard

Color : Yellow

Device Type : Straight Blade
Outlet

NEMA : 6-20R

Standards and Certifications

ANSI : C-73

CSA : C22.2 No. 42

NEMA : WD-6

NOM : 057

UL : 498

Warranty : Limited Lifetime
Warranty

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: 	
JOB NUMBER: 		

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·

FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 ·

Visit our Website at: www.leviton.com

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/company/about-leviton/locations

© 2026 Leviton Manufacturing Co., Inc.