

# DSL01-1LI

Decora Slide Dimmer Switch for Dimmable LED, CFL, and Incandescent Lighting

Replace a wall light switch with a Decora Slide dimmer switch. 150W LED, CFL incandescent, halogen, 60Hz, single pole or 3-way installation. No neutral wire required, use with Decora wallplate or Decora Plus Screwless Wallplate sold separately – Ivory



Color :  Ivory

UPC Code : 78477030882

Country Of Origin : China

## Available Colors :

 Light Almond  
 White

- PERFORMANCE YOU CAN TRUST – Affordable control engineered to match the performance of high-end dimmers
- EASY TO INSTALL – No neutral required for install and ultra-slim design at .82" fits in different wallbox and multi-gang applications
- LED ADVANCED - Superior dimming of LED bulbs and fixtures ensures flicker-free lighting
- CUSTOMIZEABLE – Setup button to optionally adjust dimmer settings and fine-tunes performance, including minimum dim, maximum bright, fade on, and startup configuration
- 3-WAY CONTROL – Convenient control of the same lights from two separate locations; use the dimmer in one location and a 3-way switch (sold separately) in the second location

To find out which LED bulbs pair best, visit our online LED Compatibility Tool by clicking the "find an LED bulb" button below.

## Technical Information

### Product Features

**Action :** Rocker Switch for ON /OFF, slide bar for lighting level control

**Available Colors :** White, Ivory, Light Almond

**Color :** Ivory

**Warranty :** 5-Year Limited

### Electrical Specifications

**Frequency :** 60 Hz

**Load Rating :** 150W LED, CFL, Incandescent, Halogen

**Load Type :** Incandescent, Halogen, Dimmable LED, Dimmable CFL

**Type :** Electro-Mechanical

**Voltage :** 120 VAC

### Mechanical Specifications

**Action :** Rocker Switch for ON /OFF, slide bar for lighting level control

**Preset :** Integrated slider to brighten and dim lights and set the preferred light level

**Protection :** Radio/TV Filter

**Locator Light :** Green locator light disabled by default

**Style Name :** Decora Slide

### Environmental Specifications

**Operating Temperature :** 0°C – 40°C

**Relative Humidity :** 10% - 90%, non-condensing

**Storage Temperature Range :** -10°C – 85°C

**Switch Type :** Single-Pole & 3-Way

**Wallplate :** Order Separately

#### Standards & Certifications

##### **Standards and Certifications**

: cULus, FCC/IC, Complies with California Title 24 Part 6, IECC 2021 and 2024, SSL7A

## **Features and Benefits**

### **Benefits:**

- PERFORMANCE YOU CAN TRUST – Affordable control engineered to match the performance of high-end dimmers.
- EASY TO INSTALL – No neutral required for install and ultra-slim design fits in different wallbox and multi-gang applications.
- LED ADVANCED - Superior dimming of LED bulbs and fixtures ensures flicker-free lighting .
- CUSTOMIZEABLE – Setup button to optionally adjust dimmer settings and fine-tunes performance, including minimum dim, maximum bright, fade on, and startup configuration.
- 3-WAY CONTROL – Convenient control of the same lights from two separate locations; use the dimmer in one location and a 3-way switch (sold separately) in the second location.

### **Features:**

- LED Advanced Dimming Technology provides superior dimming of LED bulbs and fixtures to ensure flicker-free results with no customer complaints.
- Setup button to optionally adjust dimmer settings and fine-tunes performance, including minimum dim, maximum bright, fade on, and startup configuration.
- Color Change Kits to match any project aesthetic with 7 color change options.
- Integrated slider to brighten and dim lights and set the preferred light level.
- Separate switch to turn the lights On and OFF.
- No neutral wire required for installation.
- Easily change the color using DSKIT faceplates available in white, ivory, light almond, gray, black, brown and red.

To find out which LED bulbs pair best, visit our online LED Compatibility Tool by clicking the "find an LED bulb" button below.

## **Patents\***

US11903105

MX321054

US9431192

US8664886

CA2798964

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

#### SPECIFICATION SUBMITTAL

|                                            |                                                 |                      |
|--------------------------------------------|-------------------------------------------------|----------------------|
| <b>JOB NAME:</b><br><input type="text"/>   | <b>CATALOG NUMBERS:</b><br><input type="text"/> |                      |
| <b>JOB NUMBER:</b><br><input type="text"/> | <input type="text"/>                            | <input type="text"/> |

#### **Leviton Manufacturing Co., Inc**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

#### **Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·

FAX: +1-800-824-3005 ·

#### **Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 ·

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

#### **Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/company/about-leviton/locations](http://www.leviton.com/company/about-leviton/locations)

© 2026 Leviton Manufacturing Co., Inc.