



Color :  White

UPC Code : 78477030899

Country Of Origin : China

Available Colors :

 Light Almond
 Ivory

DSL01-1LW

Decora Slide Dimmer Switch for Dimmable LED, CFL, and Incandescent Lighting

Replace a wall light switch with a Decora Slide dimmer switch. 150W LED, CFL incandescent, halogen, 60Hz, single pole or 3-way installation. No neutral wire required, use with Decora wallplate or Decora Plus Screwless Wallplate sold separately – White

- PERFORMANCE YOU CAN TRUST – Affordable control engineered to match the performance of high-end dimmers
- EASY TO INSTALL – No neutral required for install and ultra-slim design at .82" fits in different wallbox and multi-gang applications
- LED ADVANCED - Superior dimming of LED bulbs and fixtures ensures flicker-free lighting
- CUSTOMIZEABLE – Setup button to optionally adjust dimmer settings and fine-tunes performance, including minimum dim, maximum bright, fade on, and startup configuration
- 3-WAY CONTROL – Convenient control of the same lights from two separate locations; use the dimmer in one location and a 3-way switch (sold separately) in the second location

To find out which LED bulbs pair best, visit our online LED Compatibility Tool by clicking the "find an LED bulb" button below.

Technical Information

Product Features

Action : Rocker Switch for ON /OFF, slide bar for lighting level control

Available Colors : White, Ivory, Light Almond

Color : White

Warranty : 5-Year Limited

Electrical Specifications

Frequency : 60 Hz

Load Rating : 150W LED, CFL, Incandescent, Halogen

Load Type : Incandescent, Halogen, Dimmable LED, Dimmable CFL

Type : Electro-Mechanical

Voltage : 120 VAC

Mechanical Specifications

Action : Rocker Switch for ON /OFF, slide bar for lighting level control

Preset : Integrated slider to brighten and dim lights and set the preferred light level

Protection : Radio/TV Filter

Locator Light : Green locator light disabled by default

Style Name : Decora Slide

Environmental Specifications

Operating Temperature : 0°C – 40°C

Relative Humidity : 10% - 90%, non-condensing

Storage Temperature Range : -10°C – 85°C

Switch Type : Single-Pole & 3-Way

Wallplate : Order Separately

Standards & Certifications

Standards and Certifications

: cULus, FCC/IC, Complies with California Title 24 Part 6, IECC 2021 and 2024, SSL7A

Features and Benefits

Benefits:

- PERFORMANCE YOU CAN TRUST – Affordable control engineered to match the performance of high-end dimmers.
- EASY TO INSTALL – No neutral required for install and ultra-slim design fits in different wallbox and multi-gang applications.
- LED ADVANCED - Superior dimming of LED bulbs and fixtures ensures flicker-free lighting .
- CUSTOMIZEABLE – Setup button to optionally adjust dimmer settings and fine-tunes performance, including minimum dim, maximum bright, fade on, and startup configuration.
- 3-WAY CONTROL – Convenient control of the same lights from two separate locations; use the dimmer in one location and a 3-way switch (sold separately) in the second location.

Features:

- LED Advanced Dimming Technology provides superior dimming of LED bulbs and fixtures to ensure flicker-free results with no customer complaints.
- Setup button to optionally adjust dimmer settings and fine-tunes performance, including minimum dim, maximum bright, fade on, and startup configuration.
- Color Change Kits to match any project aesthetic with 7 color change options.
- Integrated slider to brighten and dim lights and set the preferred light level.
- Separate switch to turn the lights On and OFF.
- No neutral wire required for installation.
- Easily change the color using DSKIT faceplates available in white, ivory, light almond, gray, black, brown and red.

To find out which LED bulbs pair best, visit our online LED Compatibility Tool by clicking the "find an LED bulb" button below.

Patents *

US11903105

US9431192

CA2798964

MX321054

US8664886

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: 	
JOB NUMBER: 		

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·

FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 ·

Visit our Website at: www.leviton.com

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/company/about-leviton/locations

© 2026 Leviton Manufacturing Co., Inc.