



**Color :**  Brown

**UPC Code :** 078477029565

**Country Of Origin :** Mexico

**NEMA :**  5-15R

#### Available Colors :



# DTC15

15 Amp Decora Plus Duplex Receptacle/Outlet, Commercial Grade, Tamper-Resistant, Self-Grounding

Decora Plus Duplex Receptacle Outlet, Commercial Specification Grade, Smooth Face, 15 Amp, 125 Volt, Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Tamper-Resistant, Self-Grounding - Brown

**ROHS Compliant :** Yes

These Commercial Grade devices are the electrical contractor's choice for use in hotels, schools, hospitals and commercial office buildings.

## Technical Information

### Standards and Certifications

**ANSI :** C-73

**NEMA :** WD-1 & WD-6

**NOM :** 057

**Applicable Standards :** UL 498| Fed Spec W-C-595G| CSA C22.2 No. 42

**Warranty :** 10-Year Limited

### Product Features

**Color :** Brown

**Device Type :** Duplex Receptacle Outlet

**Feature :** Smooth Face

**Feature :** Tamper-Resistant

**Grade :** Commercial Specification Grade

**Grounding :** Self-Grounding

**NEMA :** 5-15R

### Electrical Specifications

**Amperage :** 15 A

**Current Limiting :** Full Rated Current

**Dielectric Voltage :** Withstands 2000V per UL498

**Grounding :** Self-Grounding

**Pole :** 2

**Temperature Rise :** Max 30C after 100 cycles OL at 150 percent rated current

**Voltage :** 125 VAC

**Wire :** 3

### Environmental Specifications

**Operating Temperature :** -40° C to 60°C

**Flammability :** Rated V-2 per UL94

### Material Specifications

**Body Material :** Nylon

**Color :** Brown

**Face Material :** Nylon

**Ground Clips :** Brass-Plated

**Grounding Screw :** Steel 8-32

### Mechanical Specifications

**Product ID :** Ratings are permanently marked on device

**Terminal Accom. :** 14-10 AWG

**Terminal ID :** Brass-Hot, Green-Ground, Silver-Neutral

**Line Contacts** : Brass Double  
Wipe .031 Thick

**Strap Material** : Zinc-Plated  
Steel

**Terminal Screws** : Steel 8-32

AC Horsepower Ratings

**At Rated Voltage** : 1/2 HP

**Termination** : Side Wire

**Screw Terminal Torque** : 14-  
18 in-lbs

**SPECIFICATION SUBMITTAL**

|                                            |                                                 |                      |
|--------------------------------------------|-------------------------------------------------|----------------------|
| <b>JOB NAME:</b><br><input type="text"/>   | <b>CATALOG NUMBERS:</b><br><input type="text"/> |                      |
| <b>JOB NUMBER:</b><br><input type="text"/> | <input type="text"/>                            | <input type="text"/> |

**Leviton Manufacturing Co., Inc**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.  
T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·  
FAX: +1-800-824-3005 ·

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)  
5386- 1797 ·

**Visit our Website at:** [www.leviton.com](http://www.leviton.com)

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without  
notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:  
[www.leviton.com/company/about-leviton/locations](http://www.leviton.com/company/about-leviton/locations)

© 2026 Leviton Manufacturing Co., Inc.