



Color :  Red

UPC Code : 078477553015

Country Of Origin : Mexico

NEMA :  5-15R

Available Colors :



Gray



Ivory



Light Almond



White

M8200-ILR

Lev-Lok Duplex Receptacle

Lev-Lok Duplex Receptacle Outlet, Extra Heavy-Duty Hospital Grade, Illuminated, Smooth Face, 15 Amp, 125 Volt, Modular, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - Red **Mating Lev-Lok Wiring Module Required for Use**

[Lev-Lok Savings Calculator](#)

Technical Information

AC Horsepower Ratings

Horsepower Rating : 1/2 HP

Electrical Specifications

Amperage : 15 A

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Self-Grounding

Illumination : 100,000 HR
Green LED's

Pole : 2

Temperature Rise : Max 30C
after 250 cycles OL at 200
percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-2 per
UL94

Operating Temperature : -40°
C to 60°C

Material Specifications

Body Material : Nylon

Face Material : Nylon

Ground Clips : Brass

Line Contacts : 0.040" Brass

Locking Pins : Solid Brass

Shutter Mechanism : Delrin®
Acetal

Strap Material : Nickel Plated
Brass

Mechanical Specifications

Lead Identification : Leads
identified in accordance with UL
498 (black, white & green)

Product ID : Markings are
permanently marked on device

Termination : Modular

Product Features

Brand : Lev-Lok

Color : Red

Device Type : Duplex
Receptacle Outlet

Feature 3 : Illuminated

Feature 4 : Smooth Face

Grade : Extra Heavy-Duty
Hospital Grade

NEMA : 5-15R

Standards and Certifications

ANSI : C-73

CSA : 152105

NEMA : WD-6

NOM : 057

RoHS : Compliant

UL 498 and Fed Spec WD496
: E13399

Warranty : 10-Year Limited

Patents *

CA2762851

MX324425

US9112321

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: 	
JOB NUMBER: 		

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·

FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/company/about-leviton/locations

© 2026 Leviton Manufacturing Co., Inc.