



MRI83-GY

MRI Duplex Receptacle

MRI Duplex Receptacle Outlet, Extra Heavy-Duty Hospital Grade, Smooth Face, 20 Amp, 125 Volt, Back or Side Wire, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - Gray

Technical Information

AC Horsepower Ratings

Horsepower Rating : 1 HP

Electrical Specifications

Amperage : 20 A

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Self-Grounding

Pole : 2

Temperature Rise : Max 30C
after 250 cycles OL at 200 percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-2 per UL94

Operating Temperature : -40° C to 60°C

Material Specifications

Body Material : Nylon

Clamp Nuts : Brass

Face Material : Nylon

Ground Clips : Brass

Grounding Screw : Brass 8-32

Line Contacts : Brass Triple Wipe .031 Thick

Terminal Screws : Brass 10-32

Yoke : Brass

Mechanical Specifications

Product ID : Ratings are permanently marked on device

Terminal Accom. : 14-10 AWG

Terminal ID : Brass-Hot, Green-Ground, White-Neutral

Termination : Back or Side Wire

Product Features

Amperage : 20 A

Body Material : Nylon

Color : Gray

Device Type : Duplex Receptacle Outlet

Face Material : Nylon

Feature 4 : Smooth Face

Function : MRI

Grade : Extra Heavy-Duty Hospital Grade

Color :  Gray

UPC Code : 078477473597

Country Of Origin : Please Contact Customer Service

NEMA :  5-20R

Available Colors :

 Ivory
 Red
 Light Almond
 White

Grounding : Self-Grounding

NEMA : 5-20R

Pole : 2

Standards and Certifications
: UL/CSA

Strap Material : Brass

Voltage : 125 VAC

Warranty : 10-Year Limited

Wire : 3

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 42 : File
152105

NEMA : WD-6


NOM : 057

UL Fed Spec WC-596 : File
E13399

UL498HG : File E13399

Warranty : 10-Year Limited

Wiring Diagram



SPECIFICATION SUBMITTAL

JOB NAME:

JOB NUMBER:

CATALOG NUMBERS:

--	--

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/company/about-leviton/locations

© 2026 Leviton Manufacturing Co., Inc.