


SPECIFICATION

NEXLEDS®
NEXLEDS LTD



5 CCT
Changeable

VIDEO



25W:
35W:
45W:

2700K

2280 LM
3204 LM
4048 LM

3000K

2351 LM
3312 LM
4313 LM

3500K

2436 LM
3453 LM
4438 LM

4000K

2464 LM
3510 LM
4486 LM

5000K

2492 LM
3500 LM
4460 LM

10" Split Deep Regress Commercial Downlight

NX-CDL-E2T10-45W-5C-DV

Specification

PRODUCT NAME :	10" Split Deep Regress Commercial Downlight
MODEL NO. :	NX-CDL-E2T10-45W-5C-DV
SPECIFICATION :	TYPE IC; AC120-347V; 50/60Hz; 25W-35W-45W
WORKING TEMP :	-4(°F)~+122(°F)
POWER FACTOR :	>0.90
CRI(RA) :	>90
COLOR :	Silver Color
LIGHT SOURCE :	SMD2835 Chip
LUMEN :	4486lm
LIFE TIME :	50000 hrs
BEAM ANGLE :	50°
PRODUCT SIZE :	D(11.46inch)*H(6inch)
CUT OUT SIZE :	9.97 inch
IP :	Suitable for wet location
APPLICATION :	School, Shopping Center, Hotel
WARRANTY :	5 years
STANDARD :	ETL
DIMMABLE :	0-10V Dimming
COLOR TEMP :	2700K-3000K-3500K-4000K-5000K Changleable



www.nexleds.ca



Email: sales@nexleds.ca

NEXLEDS®

NEXLEDS LTD

Feature:

- Spun aluminum reflector integrate with haze finish and white trim ring with shadow free.
- Durable tension clips, allow for fast and easy flush installation.
- 0-10V dimmable.
- Available in 3 wattages and 5 CCT tunable.
- LED split deep regress commercial downlight series are available in 3 different light engine. Each light engine could fitting 6" , 8" , 10" round trims.
- The innovative separable design of junction box and trim makes it more flexible. One engine allows for seamless integration of multiple trim sizes with easy and tool-free installation.
- Easy-fit installation comes from the adjustable butterfly clips. It is designed for recessed application.
- It is suitable for commercial and public places and elegantly decorates the ambience, such as shopping mall, hospital, airport, hotel lobby etc.



Selectable CCT & Selectable Wattage

The innovative separable design of junction box and trim makes it more flexible.

Easy-fit installation comes from the adjustable butterfly clips.



Dimension:

	6" Light Engine (15W-20W-25W)	8" Light Engine (25W-35W-45W)	10" Light Engine (45W-55W-65W)	Hole Cutout
6" Round Trim				
8" Round Trim				
10" Round Trim				

