

NOARK

# A25H4DV800

ACB - 1800699 - UL1066 - 2500A frame - 4P4d - 800A rated - withdrawable vertical connection - 800Vac - 100kA

Withdrawable / drawout Air Circuit Breaker (ACB) - UL1066 - NOARK (A25 series) - 4-poles (4P4d) - Rated current 800A - Interrupting capacity 100kA (254-508Vac) - Withdrawable / drawout chassis with rear vertical connection pads - equivalent to 1800699

## Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

## Specifications

| | |
|---|---|
| **Primary brand** | NOARK |
| **Main function** | Air Circuit Breaker (ACB) |
| **Product series / family name** | Electrical protection > Circuit breakers > Air Circuit Breakers (ACBs) > Draw-out/withdrawable |
| **Sub-range name** | A25 series |
| **Functions** | Withdrawable / drawout Air Circuit Breaker (ACB) |
| **Poles** | 4-poles (4P4d) |
| **Rated current** | 800A |
| **Rated voltage (AC)** | 800Vac (50/60Hz) |
| **Connection type** | Withdrawable / drawout chassis with rear vertical connection pads (more advanced electrical circuits mechanical design; lower breaker derating) |
| **Short circuit breaking rating** | 100kA (254-508Vac)<br>85kA (635-847Vac) |
| **Short circuit withstand current (Icw)** | 85kA (480Vac)<br>85kA (480Vac)<br>85kA (600Vac)<br>85kA (800Vac) |
| **Dimensions** | H460mm x W452mm x D430mm<br>H18.113" x W17.8" x D16.93"<br>H530mm x W545mm x D465mm (H20.87" x W21.46" x D18.31") enclosure dimensions |

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

# A25H4DV800

ACB - 1800699 - UL1066 - 2500A frame - 4P4d - 800A rated - withdrawable vertical connection - 800Vac - 100kA

| | |
|---|---|
| **Order code / Manufacturer SKU** | A25H4DV800<br>1800699 |
| **Manufacturer product status** | Commercialized |
| **Equivalent to** | 1800699 |
| **Compliant with standard(s)** | UL1066<br>UL1066 (low-voltage AC and DC power circuit breakers)<br>CSA C22.2 No.31<br>ANSI C37.13 (low-voltage power circuit breakers)<br>ANSI C37.16 (low-voltage power circuit breakers ratings; related requirements and applications)<br>ANSI C37.17 (IEEE standard for trip systems)<br>ANSI C37.50 (low-voltage AC power circuit breakers; test procedure) |
| **Electrical durability** | (635Vac) 600 hours<br>(847Vac) 300 hours |
| **Mechanical durability** | 10000 hours |

## Documents

NOARK - Power Circuit Breakers and Non-Automatic Switches - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com