

NOARK

A25Q4DV600

ACB - 1800614 - UL1066 - 2500A frame - 4P4d - 600A rated - withdrawable vertical connection - 800Vac - 65kA

Withdrawable / drawout Air Circuit Breaker (ACB) - UL1066 - NOARK (A25 series) - 4-poles (4P4d) - Rated current 600A - Interrupting capacity 65kA (254-847Vac) - Withdrawable / drawout chassis with rear vertical connection pads - equivalent to 1800614

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Air Circuit Breaker (ACB)
Product series / family name	Electrical protection > Circuit breakers > Air Circuit Breakers (ACBs) > Draw-out/withdrawable
Sub-range name	A25 series
Functions	Withdrawable / drawout Air Circuit Breaker (ACB)
Poles	4-poles (4P4d)
Rated current	600A
Rated voltage (AC)	800Vac (50/60Hz)
Connection type	Withdrawable / drawout chassis with rear vertical connection pads (more advanced electrical circuits mechanical design; lower breaker derating)
Short circuit breaking rating	65kA (254-847Vac)
Short circuit withstand current (Icw)	65kA (480Vac) 65kA (480Vac) 65kA (600Vac) 65kA (800Vac)
Dimensions	H460mm x W452mm x D430mm H18.113" x W17.8" x D16.93" H530mm x W545mm x D465mm (H20.87" x W21.46" x D18.31") enclosure dimensions
Order code / Manufacturer SKU	A25Q4DV600 1800614

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

A25O4DV600

ACB - 1800614 - UL1066 - 2500A frame - 4P4d - 600A rated - withdrawable vertical connection - 800Vac - 65kA

Manufacturer product status	Commercialized
Equivalent to	1800614
Compliant with standard(s)	UL1066 UL1066 (low-voltage AC and DC power circuit breakers) CSA C22.2 No.31 ANSI C37.13 (low-voltage power circuit breakers) ANSI C37.16 (low-voltage power circuit breakers ratings; related requirements and applications) ANSI C37.17 (IEEE standard for trip systems) ANSI C37.50 (low-voltage AC power circuit breakers; test procedure)
Electrical durability	(635Vac) 600 hours (847Vac) 300 hours
Mechanical durability	10000 hours

Documents

NOARK - Power Circuit Breakers and Non-Automatic Switches - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com