

NOARK

AL/AX21P

Alarm (AL) ON/OFF and TRIP signalling contact/switch - 1100554 - for M1/M2/M3/M4/M5/M6 - 1NO+1NC

Auxiliary combined ON/OFF and TRIP signalling contact / switch block - for UL489 devices (M1-M6 models) - NOARK - 1NO+1NC (1 Normally Open + 1 Normally Closed) aux. contacts - equivalent to 1100554 / ALAX21P

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Auxiliary contact
Product series / family name	Electrical protection > MCCBs and disconnector switches accessories > Auxiliary controls
Functions	Auxiliary combined ON/OFF and TRIP signalling contact / switch block
Rated current	5A (240Vac) 2A (480Vac) 0.25A (110Vdc) 0.25A (220Vdc)
Normally Open (NO) auxliary contacts	1 NO contacts
Normally Closed (NC) auxiliary contacts	1 NC contacts
Contacts type	1NO+1NC (1 Normally Open + 1 Normally Closed) aux. contacts
Dimensions	H29.5mm x W31.5mm x D12.7mm H1.16" x W1.24" x D0.5"
Technical compatibility with	for UL489 devices (M1-M6 models)
Order code / Manufacturer SKU	AL/AX21P 1100554
Manufacturer product status	Commercialized
Equivalent to	1100554 ALAX21P

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Documents

E-PLAN - NOARK - AL/AX21P - Part details

NOARK - MCCB MCP MCS Ex9 series-M - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com