

NOARK

AL3111L

Alarm (AL) ON/OFF and TRIP signalling contact/switch UL1077 - 1002612 - 1NO+1NC - 480Vac/130Vdc

Auxiliary combined ON/OFF and TRIP signalling contact / switch block - for 80-125A rated current UL1077 devices - NOARK - 480Vac / 130Vdc rated voltage - 1NO+1NC (1 Normally Open + 1 Normally Closed) aux. contacts - DIN rail mounting (35mm width) - equivalent to 1002612

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Auxiliary contact
Product series / family name	Electrical protection > MCBs accessories > UL1077 > Aux. contacts
Functions	Auxiliary combined ON/OFF and TRIP signalling contact / switch block
Design	for 80-125A rated current UL1077 devices
Rated current	1A (130Vdc) 2A (48Vdc) 3A (227Vac / 415Vac / 480Vac) 6A (240Vac / 24Vdc) 12A (120Vac / 12Vdc) 24A (6Vdc)
Rated Voltage (DC)	130Vdc
Rated voltage (AC)	480Vac
Mounting mode	DIN rail
Normally Open (NO) auxliary contacts	1 NO contacts
Normally Closed (NC) auxiliary contacts	1 NC contacts
Contacts type	1NO+1NC (1 Normally Open + 1 Normally Closed) aux. contacts
Dimensions	H88.9mm x W10.16mm x D76.2mm H3.2" x W0.4" x D3"
Net Width (mm)	35 mm

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Order code / Manufacturer SKU	AL3111L 1002612
Manufacturer product status	Commercialized
Equivalent to	1002612
Compliant with standard(s)	UL 1077

Documents

NOARK - Essential components catalog (circuit protection & motor controls & pilot devices) - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com