

NOARK

AX3111L

Auxiliary (AX) ON/OFF contact/switch UL1077 - 1002611 - 1NO+1NC - 480Vac/130Vdc

Auxiliary ON/OFF contact / switch block - for 80-125A rated current UL1077 devices - NOARK - 480Vac / 130Vdc rated voltage - 1NO+1NC (1 Normally Open + 1 Normally Closed) aux. contacts - DIN rail mounting (35mm width) - equivalent to 1002611

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Auxiliary contact
Product series / family name	Electrical protection > MCBs accessories > UL1077 > Aux. contacts
Functions	Auxiliary ON/OFF contact / switch block
Design	for 80-125A rated current UL1077 devices
Rated current	1A (130Vdc) 2A (48Vdc) 3A (227Vac / 415Vac / 480Vac) 6A (240Vac / 24Vdc) 12A (120Vac / 12Vdc) 24A (6Vdc)
Rated Voltage (DC)	130Vdc
Rated voltage (AC)	480Vac
Mounting mode	DIN rail
Normally Open (NO) auxliary contacts	1 NO contacts
Normally Closed (NC) auxiliary contacts	1 NC contacts
Contacts type	1NO+1NC (1 Normally Open + 1 Normally Closed) aux. contacts
Dimensions	H88.9mm x W10.16mm x D76.2mm H3.2" x W0.4" x D3"
Net Width (mm)	35 mm

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Order code / Manufacturer SKU	AX3111L 1002611
Manufacturer product status	Commercialized
Equivalent to	1002611
Compliant with standard(s)	UL 1077
Tightening torque	9lb.in / 1 N.m

Documents

NOARK - Essential components catalog (circuit protection & motor controls & pilot devices) - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com