

NOARK

AX4113UL

Auxiliary contact - 1330002 - Ex9CS - mounts on 6A-12A cont. - 1NO+3NC

Miniature auxiliary contact block / switch block - mounts on 6A-12A cont. - NOARK (Ex9CS series) - 1NO+3NC (1 Normally Open + 3 Normally Closed) aux. contacts - Lift term. connection - top mounting - IP20 - equivalent to 1330002

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Auxiliary contact
Product series / family name	Industrial controls > Contactors > Standard contactors > Accessories > Auxiliary contacts
Sub-range name	Ex9CS series
Functions	Miniature auxiliary contact block / switch block
Design	mounts on 6A-12A cont.
Rated current	1.9A (380Vac/400Vac/415Vac; AC-15) 0.31A (220Vdc/250Vdc; DC-15) 10A (Ith conventional free air thermal current)
Rated power	720VA (AC-15) switching 69W (DC-13) switching
Rated impulse voltage (Uimp)	6 kV
Rated insulation voltage (Ui)	690 V
Connection type	Lift term. connection
Cross-section	for #18AWG...#12AWG / 1mm2...4mm2 conductors
Mounting mode	top mounting
Normally Open (NO) auxliary contacts	1 NO contacts
Normally Closed (NC) auxiliary contacts	3 NC contacts

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

AX4113UL

Auxiliary contact - 1330002 - Ex9CS - mounts on 6A-12A cont. - 1NO+3NC

Contacts type	1NO+3NC (1 Normally Open + 3 Normally Closed) aux. contacts
Degree of protection	IP20
Dimensions	H39mm x W33mm x D37mm H1.54" x W1.3" x D1.46"
Order code / Manufacturer SKU	AX4113UL 1330002
Manufacturer product status	Commercialized
Equivalent to	1330002
Compliant with standard(s)	UL 508 (file number E353866) IEC 60947-5-1 EN 60947-5-1 CSA CCC RoHS compliant
Tightening torque	0.8 N.m

Documents

E-PLAN - NOARK - AX4113UL - Part details

NOARK - Industrial controls - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com