

NOARK

AX4231UL

Auxiliary contact - 1330012 - Ex9C - mounts on 9A-150A cont. - 3NO+1NC

Auxiliary contact block / switch block - mounts on 9A-150A cont. - NOARK (Ex9C series) - 3NO+1NC (3 Normally Open + 1 Normally Closed) aux. contacts - Lift term. connection - top mounting - IP20 - equivalent to 1330012

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Auxiliary contact
Product series / family name	Industrial controls > Contactors > Standard contactors > Accessories > Auxiliary contacts
Sub-range name	Ex9C series
Functions	Auxiliary contact block / switch block
Design	mounts on 9A-150A cont.
Rated current	1.9A (380Vac/400Vac/415Vac; AC-15) 0.31A (220Vdc/250Vdc; DC-15) 10A (Ith conventional free air thermal current)
Rated power	720VA (AC-15) switching 69W (DC-13) switching
Rated impulse voltage (Uimp)	6 kV
Rated insulation voltage (Ui)	690 V
Connection type	Lift term. connection
Cross-section	for #18AWG...#12AWG / 1mm2...4mm2 conductors
Mounting mode	top mounting
Normally Open (NO) auxliary contacts	3 NO contacts
Normally Closed (NC) auxiliary contacts	1 NC contacts

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Contacts type	3NO+1NC (3 Normally Open + 1 Normally Closed) aux. contacts
Degree of protection	IP20
Dimensions	H37mm x W48mm x D45mm H1.46" x W1.89" x D1.77"
Order code / Manufacturer SKU	AX4231UL 1330012
Manufacturer product status	Commercialized
Equivalent to	1330012
Compliant with standard(s)	UL 508 (file number E353866) IEC 60947-5-1 EN 60947-5-1 CSA CCC RoHS compliant
Tightening torque	1.7 N.m

Documents

E-PLAN - NOARK - AX4231UL - Part details

NOARK - Industrial controls - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com