

NOARK

# AX4311UL

Auxiliary contact - 1330014 - Ex9C - mounts on 9A-100A cont. - 1NO+1NC

Auxiliary contact block / switch block - mounts on 9A-100A cont. - NOARK (Ex9C series) - 1NO+1NC (1 Normally Open + 1 Normally Closed) aux. contacts - Lift term. connection - side mounting - IP20 - equivalent to 1330014

## Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

## Specifications

| | |
|---|---|
| **Primary brand** | NOARK |
| **Main function** | Auxiliary contact |
| **Product series / family name** | Industrial controls > Contactors > Standard contactors > Accessories > Auxiliary contacts |
| **Sub-range name** | Ex9C series |
| **Functions** | Auxiliary contact block / switch block |
| **Design** | mounts on 9A-100A cont. |
| **Rated current** | 6A (24Vac; AC-15)<br>3.13A (230Vac; AC-15)<br>1.8A (400Vac; AC-15)<br>1.04A (690Vac; AC-15)<br>0.55A (125Vdc; DC-13)<br>0.27A (250Vdc; DC-13)<br>10A (Ith conventional free air thermal current) |
| **Rated power** | 720VA (AC-15) switching<br>69W (DC-13) switching |
| **Rated impulse voltage (Uimp)** | 6 kV |
| **Rated insulation voltage (Ui)** | 690 V |
| **Connection type** | Lift term. connection |
| **Cross-section** | for #18AWG...#12AWG / 1mm2...4mm2 conductors |
| **Mounting mode** | side mounting |

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

| | |
|---|---|
| **Normally Open (NO) auxliary contacts** | 1 NO contacts |
| **Normally Closed (NC) auxiliary contacts** | 1 NC contacts |
| **Contacts type** | 1NO+1NC (1 Normally Open + 1 Normally Closed) aux. contacts |
| **Degree of protection** | IP20 |
| **Dimensions** | H69mm x W10mm x D70mm<br>H2.72" x W0.39" x D2.76" |
| **Order code / Manufacturer SKU** | AX4311UL<br>1330014 |
| **Manufacturer product status** | Commercialized |
| **Equivalent to** | 1330014 |
| **Compliant with standard(s)** | UL 508 (file number E353866)<br>IEC 60947-5-1<br>EN 60947-5-1<br>CSA<br>CCC<br>RoHS compliant |
| **Tightening torque** | 1.7 N.m |

## Documents

E-PLAN - NOARK - AX4311UL - Part details

NOARK - Industrial controls - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com