

NOARK

AXA13

Auxiliary contact - 1311713 - Ex9CD - mounts on 9A-630A cont. - 1NO+3NC

Auxiliary contact block / switch block - mounts on 9A-630A cont. - NOARK (Ex9CD series) - 1NO+3NC (1 Normally Open + 3 Normally Closed) aux. contacts - front mounting - IP20 - equivalent to 1311713

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Auxiliary contact
Product series / family name	Industrial controls > Contactors > Standard contactors > Accessories > Auxiliary contacts
Sub-range name	Ex9CD series
Functions	Auxiliary contact block / switch block
Design	mounts on 9A-630A cont.
Rated current	1.9A (380Vac/400Vac/415Vac; AC-15) 0.31A (220Vdc/250Vdc; DC-15) 10A (Ith conventional free air thermal current)
Rated power	720VA (AC-15) switching 69W (DC-13) switching
Rated impulse voltage (Uimp)	6 kV
Rated insulation voltage (Ui)	690 V
Mounting mode	front mounting
Normally Open (NO) auxliary contacts	1 NO contacts
Normally Closed (NC) auxiliary contacts	3 NC contacts
Contacts type	1NO+3NC (1 Normally Open + 3 Normally Closed) aux. contacts
Degree of protection	IP20

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Dimensions	H48mm x W45mm x D39mm H1.89" x W1.77" x D1.54"
Order code / Manufacturer SKU	AXA13 1311713
Manufacturer product status	Commercialized
Equivalent to	1311713
Compliant with standard(s)	UL 508 (file number E353866) IEC 60947-5-1 EN 60947-5-1 CSA CCC RoHS compliant

Documents

NOARK - Industrial controls - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com