

NOARK

AXB02

Auxiliary contact - 1311717 - Ex9CM - mounts on 6A-12A cont. - 2NC

Miniature auxiliary contact block / switch block - mounts on 6A-12A cont. - NOARK (Ex9CM series) - 2NC (2 Normally Closed) aux. contacts - front mounting - IP20 - equivalent to 1311717

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Auxiliary contact
Product series / family name	Industrial controls > Contactors > Standard contactors > Accessories > Auxiliary contacts
Sub-range name	Ex9CM series
Functions	Miniature auxiliary contact block / switch block
Design	mounts on 6A-12A cont.
Rated current	1.9A (380Vac/400Vac/415Vac; AC-15) 0.31A (220Vdc/250Vdc; DC-15) 10A (Ith conventional free air thermal current)
Rated power	720VA (AC-15) switching 69W (DC-13) switching
Rated impulse voltage (Uimp)	6 kV
Rated insulation voltage (Ui)	690 V
Mounting mode	front mounting
Normally Open (NO) auxliary contacts	0 NO contacts
Normally Closed (NC) auxiliary contacts	2 NC contacts
Contacts type	2NC (2 Normally Closed) aux. contacts
Degree of protection	IP20

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Dimensions	H33mm x W37mm x D39mm H1.3" x W1.46" x D1.54"
Order code / Manufacturer SKU	AXB02 1311717
Manufacturer product status	Commercialized
Equivalent to	1311717
Compliant with standard(s)	UL 508 (file number E353866) IEC 60947-5-1 EN 60947-5-1 CSA CCC RoHS compliant

Documents

NOARK - Industrial controls - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com