

NOARK

AXFA11

Auxiliary contact - 1313990 - Ex9CD - mounts on 9A-95A cont. - 1NO+1NC

Auxiliary contact block / switch block - mounts on 9A-95A cont. - NOARK (Ex9CD series) - 1NO+1NC (1 Normally Open + 1 Normally Closed) aux. contacts - side mounting - IP20 - equivalent to 1313990

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Auxiliary contact
Product series / family name	Industrial controls > Contactors > Standard contactors > Accessories > Auxiliary contacts
Sub-range name	Ex9CD series
Functions	Auxiliary contact block / switch block
Design	mounts on 9A-95A cont.
Rated current	6A (24Vac; AC-15) 3.13A (230Vac; AC-15) 1.8A (400Vac; AC-15) 1.04A (690Vac; AC-15) 0.55A (125Vdc; DC-13) 0.27A (250Vdc; DC-13) 10A (Ith conventional free air thermal current)
Rated power	720VA (AC-15) switching 69W (DC-13) switching
Rated impulse voltage (Uimp)	6 kV
Rated insulation voltage (Ui)	690 V
Mounting mode	side mounting
Normally Open (NO) auxliary contacts	1 NO contacts
Normally Closed (NC) auxiliary contacts	1 NC contacts

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

AXFA11

Auxiliary contact - 1313990 - Ex9CD - mounts on 9A-95A cont. - 1NO+1NC

Contacts type	1NO+1NC (1 Normally Open + 1 Normally Closed) aux. contacts
Degree of protection	IP20
Dimensions	H71mm x W18mm x D70mm H2.8" x W0.71" x D2.76"
Order code / Manufacturer SKU	AXFA11 1313990
Manufacturer product status	Commercialized
Equivalent to	1313990
Compliant with standard(s)	UL 508 (file number E353866) IEC 60947-5-1 EN 60947-5-1 CSA CCC RoHS compliant

Documents

NOARK - Industrial controls - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com