

NOARK

CBB1P57P25

Comb busbar UL1077 - 1002050 - 57P - 600Vac/1000Vdc - 18mm pitch - 25mm2 - 90° bent

Comb busbar - for UL1077 1-pole devices - 90° bent - 0.71" / 18mm pitch - NOARK (CBB busbar series) - 100A (end feed) rated current - for 57 single-pole devices (57P) - 600Vac / 1000Vdc rated voltage - equivalent to 1002050

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Busbar (comb)
Product series / family name	Electrical protection > MCBs accessories > UL1077 > Busbars
Sub-range name	CBB busbar series
Functions	Comb busbar
Design	for UL1077 1-pole devices 90° bent
Poles	for 57 single-pole devices (57P)
Distance	0.71" / 18mm pitch
Rated current	100A (end feed) 200A (center feed)
Rated Voltage (DC)	1000Vdc
Rated voltage (AC)	600Vac
Cross-section	25mm2
Short circuit breaking rating	10kA (J-fuse rating)
Degree of protection	IP20
Dimensions	H35.4mm x W1025mm x D21.2mm H1.39" x W40.35" x D0.83"

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Order code / Manufacturer SKU	CBB1P57P25 1002050
Manufacturer product status	Commercialized
Equivalent to	1002050
Compliant with standard(s)	UL 1077 CE marking RoHS compliant

Benefits

- Complete range of UL 489 listed miniature circuit breakers up to a 63A current rating
- Breakers mount on standard 35mm DIN rail - B1NQ also provides a flush and surface mount options with additional mounting clips
- Standard ratings of 10kA at 480Y/277Vac and 10kA at 125Vdc
- Suitable for branch circuit device protection
- Trip-free design - breaker cannot be defeated by holding the handle in the ON position
- Captive screws cannot be lost
- For use in applications for which UL 1077 or CSA C22.2 No.235 are also allowed
- Field installable shunt trip and auxiliary switch subsequent mounting
- Available with provisions for ring tongue terminals
- Module width of only 0.71 in (18 mm) per pole
- Contact position indicator (red/green)
- Possibility for locking the toggle in ON or OFF position

Documents

NOARK - MCB Busbar - Datasheet.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com