


NOARK

# Ex9C50F11H

Contactor - 1321940 - Ex9C - 50A - 48-130Vac/dc - 3P (3NO) - 1NO+1NC aux. contacts

Contactor - NOARK (Ex9C series) - 3-poles (3P; 3NO) - 50A (380/400Vac; AC-3) rated current - 40.8-143Vac (48Vac-130Vac nom.; 50/60Hz; 0.85...1.1 x Uc) / 40.8-143Vdc (48Vdc-130Vdc nom.; 0.85...1.1 x Uc) coil - 1NO+1NC aux. contact - Screw connection - 22kW (380/400Vac; AC-3) / 10HP (220-240Vac; single-phase; UL) / 40HP (440-480Vac; 3-phase; UL) rated power - DIN rail mounting (35/7.5 or 75/7.5) - Direct On Line (DOL) / FVNR (Full-Voltage Non-Rv.) - IP20 - equivalent to 1321940

## Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

## Specifications

| | |
|---|---|
| **Primary brand** | NOARK |
| **Main function** | Contactor |
| **Product series / family name** | Industrial controls > Contactors > Standard contactors > DOL / FVNR |
| **Sub-range name** | Ex9C series |
| **Functions** | Contactor |
| **Poles** | 3-poles (3P; 3NO) |

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

| | |
|---|---|
| **Rated current** | 50A (380/400Vac; AC-3)<br>39A (660/690Vac; AC-3)<br>80A (690Vac; AC-1)<br>70A (24Vdc; DC-1; 1P/2P/3P series connection)<br>70A (48/75Vdc; DC-1; 1P/2P/3P series connection)<br>65A (125Vdc; DC-1; 1P series connection)<br>70A (125Vdc; DC-1; 2P/3P series connection)<br>65A (24Vdc; DC-2 to DC-5; 1P/2P/3P series connection)<br>65A (48/75Vdc; DC-2 to DC-5; 1P/2P/3P series connection)<br>4A (125Vdc; DC-2 to DC-5; 1P series connection)<br>65A (125Vdc; DC-2 to DC-5; 2P/3P series connection)<br>1.5A (225Vdc; DC-2 to DC-5; 1P series connection)<br>4A (225Vdc; DC-2 to DC-5; 2P series connection)<br>65A (225Vdc; DC-2 to DC-5; 3P series connection)<br>6A (120Vac; AC-15)<br>3A (240Vac; AC-15)<br>1.9A (380Vac; AC-15)<br>1.2A (600Vac; AC-15)<br>0.55A (125Vdc; DC-13)<br>0.31A (220Vdc; DC-13)<br>0.27A (250Vdc; DC-13)<br>80A (Ith conventional free air thermal current at 40˚C ambient)<br>80A (Ith conventional free air thermal current at 60˚C ambient)<br>60A (Ith conventional free air thermal current at 70˚C ambient) |
| **Rated active power (kW)** | 22kW (380/400Vac; AC-3)<br>15kW (230Vac; AC-3)<br>33kW (660/690Vac; AC-3) |
| **Rated power (HP)** | 40HP (440-480Vac; 3-phase; UL)<br>10HP (220-240Vac; single-phase; UL)<br>5HP (110-120Vac; single-phase; UL)<br>15HP (200-208Vac; 3-phase; UL)<br>20HP (220-240Vac; 3-phase; UL)<br>40HP (550-600Vac; 3-phase; UL) |
| **Rated operating voltage (Ue)** | (aux. contacts) 690 V |
| **Rated impulse voltage (Uimp)** | 8 kV |
| **Rated insulation voltage (Ui)** | 1000 V |
| **Connection type** | Screw connection<br>M8 screw connection (power circuits)<br>M3.5 screw connections (auxiliary contact) |
| **Cross-section** | #14AWG...#4AWG / 1.5mm2...25mm2 conductors (main power connection; bare flexible cable)<br>#14AWG...#4AWG / 1.5mm2...25mm2 conductors (main power connection; bare rigid cable)<br>#18AWG...#12AWG / 1mm2...2.5mm2 conductors (auxiliary contact terminal connection) |
| **Control Voltage (AC)** | 40.8-143Vac (48Vac-130Vac nom.; 50/60Hz; 0.85...1.1 x Uc)<br>26-36Vac drop-out (0.2Ucmax...0.75Ucmin) -- guaranteed control voltage range where contactor will always open |
| **Control Voltage (DC)** | 40.8-143Vdc (48Vdc-130Vdc nom.; 0.85...1.1 x Uc)<br>13-36Vdc drop-off (0.1Ucmax...0.75Ucmin) |

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

| | |
|---|---|
| **Mounting mode** | DIN rail mounting (35/7.5 or 75/7.5)<br>screw mounting on a plate (5mm holes) |
| **Normally Open (NO) auxliary contacts** | 1 NO contacts |
| **Normally Closed (NC) auxiliary contacts** | 1 NC contacts |
| **Response time** | (operating / closing time) 50-100ms / 0.05-0.1 s<br>(drop-off / opening time) 20-120ms / 0.02-0.12 s |
| **Contacts type** | 1NO+1NC (1 Normally Open + 1 Normally Closed) aux. contacts |
| **Degree of protection** | IP20 |
| **Dimensions** | H122mm x W76mm x L123mm<br>H4.80" x W2.99" x L4.84" |
| **Ambient air temperature for operation** | -4˚F...+140˚F / -20˚C...+60 ˚C |
| **Ambient air temperature for storage** | -76˚F...+176˚F / -60˚C...+80 ˚C |
| **Power consumption** | (DC; hold) 8 W<br>(DC; pick-up) 100 W |
| **Power consumption** | (AC; inrush) 100 VA<br>(AC; sealed) 15 VA |
| **Application type** | Direct On Line (DOL)<br>FVNR (Full-Voltage Non-Rv.)<br>6562ft / 2000m max. height above sea level |
| **Order code / Manufacturer SKU** | Ex9C50F11H<br>1321940 |
| **Manufacturer product status** | Commercialized |
| **Equivalent to** | 1321940 |
| **Compliant with standard(s)** | UL 508 (file number E353866)<br>IEC 60947<br>EN 60947<br>CSA<br>CCC<br>RoHS compliant<br>Production Standard -- IEC 60947-1<br>Production Standard -- IEC 60947-4-1<br>Production Standard -- UL 60947-1<br>Production Standard -- UL 60947-4-1<br>Environmental Testing According to IEC 60068-2-1 / IEC 60068-2-2 / IEC 60068-2-11 / IEC 60068-2-30 |
| **Electrical durability** | (AC-4; 380/400V) 30 000 hours<br>(AC-3; 380/400V) 1 200 000 hours |
| **Mechanical durability** | 10 000 000 hours |

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

| | |
|---|---|
| **Operating rate** | (AC-3) 1000 Cycles/hour<br>(AC-4) 120 Cycles/hour |
| **Tightening torque** | (main power terminal connection) 6 N.m<br>(auxiliary contact connection) 1.7 N.m |
| **Degree of pollution** | Class III |

## Benefits

Ex9C contactors are intended for various applications including heavy industrial loads.
9 frame sizes allows optimization of electrical parameters and mechanical dimensions.

A range of overload relays are available in a variety of frame sizes to fit respective contactors of given rated current.
- Nine frame sizes with rated current up to 1000A at 690V AC-3
- Coil control voltage available in AC and DC with ranges from 24-600V
- Wide range electronic coil available for 9-500A contactors features built-in surge suppression
- DIN rail 35mm and panel mountable

## Documents

E-PLAN - NOARK - Ex9C50F11H - Part details

NOARK - Industrial controls - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com