


NOARK

Ex9CKT30A20G7Q

Definite-purpose (DP) contactor - 1314444 - Ex9CKT - 30A - 120Vac (50/60Hz) - 2P (2NO)

Definite-purpose (DP) contactor - NOARK (Ex9CKT series) - 2-poles (2P; 2NO) - 30A (FLA) rated current - 120Vac (50/60Hz) coil - #10-32 screw connection with pressure plate for line and load sides + Quad FASTON Quick Connect spade connectors (4 connectors per pole) - 3HP (240Vac; single-phase) rated power - Direct On Line (DOL) / FVNR (Full-Voltage Non-Rv.) - equivalent to 1314444

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Contactor
Product series / family name	Industrial controls > Contactors > Definite purpose contactors
Sub-range name	Ex9CKT series
Functions	Definite-purpose (DP) contactor
Poles	2-poles (2P; 2NO)
Resistance (Ω)	250Ω (nominal coil resistance)
Rated current	30A (FLA) 32A (at 240/277Vac; 480Vac; 600Vac) 40A (Resistive Load Amps; 600Vac) 200A (240/277Vac; Locked Rotor Amperes) 150A (480Vac; Locked Rotor Amperes) 120A (600Vac; Locked Rotor Amperes) 40A (Tungsten & Ballast rating)
Rated power (HP)	3HP (240Vac; single-phase) 2HP (120Vac; single-phase)
Connection type	#10-32 screw connection with pressure plate for line and load sides Phillips screw Quad FASTON Quick Connect spade connectors (4 connectors per pole)
Cross-section	#12AWG...#8AWG / 6mm2...10mm2 conductors (Copper rigid cable) #14AWG...#10AWG / 2.5mm2...6mm2 conductors (Copper flexible stranded cable)

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Control Voltage (AC)	120Vac (50/60Hz) 102Vac max. pick-up voltage -- control voltage above which contactor is guaranteed to close 24Vac min. drop-out voltage -- control voltage below which contactor is guaranteed to open
Normally Open (NO) auxliary contacts	0 NO contacts
Normally Closed (NC) auxiliary contacts	0 NC contacts
Dimensions	H92mm x W55mm x D67mm H3.59" x W2.15" x D2.61"
Technical compatibility with	Recommended protection -- 50A M1N series circuit breaker or 80A class J/class L fuse
Power consumption	(inrush; 50Hz) 40 VA (inrush; 60Hz) 38.5 VA (sealed; 50Hz) 10 VA (sealed; 60Hz) 9.5 VA
Application type	Direct On Line (DOL) FVNR (Full-Voltage Non-Rv.)
Order code / Manufacturer SKU	Ex9CKT30A20G7Q 1314444
Manufacturer product status	Commercialized
Equivalent to	1314444
Compliant with standard(s)	UL 60947-4-1 UL 508 UL (file number E353866) IEC 60947-4-1 EN 60947-4-1 CSA C22.2 No.265900 CE compliant ARI-780 HVAC Insulation -- Class B 266˚F (130˚C)
Tightening torque	(main circuit) 2.3 N.m

Benefits

Ex9CKT Series DP Contactors provide high performance with both flexibility and reliability.

They are designed to match numerous applications including
- Air conditioning
- Resistive heating
- Refrigeration equipment
- Motors
- Welding
- Pumps
- Power supplies

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

- Food service equipment
- Compressors
- Business machines
- Lighting (25-50A)

Available as
- 20-40A, 1- to 4-pole available now
- Enclosed coil standard for all 1- to 4-pole frame sizes
- Industry standard mounting plate provides easily accessible mounting holes
- Connection terminal options, including screw or lug connections each with quick connect spades
- Coil is Class B 266˚F (130˚C) insulation system with a wide range of voltages and 50/60 Hz ratings
- Double E magnet assembly provides optimal performance with reduced power consumption
- Base assembly is made from high arc-resistant polyester
- 100,000 to 250,000 cycles by UL 508/UL60947-4-1 for air resistance heating application

Documents

NOARK - Industrial controls - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com