

NOARK

Ex9IL1A6

Indicator light - Ex9IL - 1200669 - Round Flat - Blue - 6Vac/dc LED

Compact pilot indicator light with LED - full-voltage input - NOARK (Ex9IL series) - Blue - 22mm (7/8") round flat / flush - Plastic body and cap - Supply voltage 6Vac / 6Vdc - IP65 - equivalent to 1200669

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Pilot light
Product series / family name	Industrial controls > Pilot devices > Pilot lights
Sub-range name	Ex9IL series
Functions	Compact pilot indicator light
Design	LED full-voltage input
Supply voltage (AC)	6Vac
Supply voltage (DC)	6Vdc
Light Color	Blue
Shape	22mm (7/8") round flat / flush
Diameter	22.5mm mounting hole diameter
Degree of protection	IP65
Dimensions	H50mm x W30mm x D30mm H1.97" x W1.18" x D1.18"
Material	Plastic body and cap
Current consumption	20mA max.
Order code / Manufacturer SKU	Ex9IL1A6 1200669
Manufacturer product status	Commercialized

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Equivalent to	1200669
Compliant with standard(s)	UL Listed (File Number E353866) CSA IEC/EN 60947 VDE 0660 CE compliant RoHS compliant
Brightness	60cd/m2

Benefits

Features
- Metal construction for superior durability and visual appeal
- UL listed and IP 40* (front) available for protection against dust and water
- Low behind the panel depth
- Operators mount in a round 7/8 in (22.5 mm) hole that is interchangeable with competitor's products
- Field convertible from maintained to momentary (available on maintained pushbuttons only)
- Modular construction makes assembly fast and simplifies stocking of components and complete devices

Documents

NOARK - 22mm Pilot Devices - Datasheet.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com