

NOARK

Ex9PBL8425

Double-headed push-button - Ex9PB - 1200439 - Momentary - Rectangular extended - Red/Green - 1NO+1NC

Double-headed pushbutton/push-button/PB - NOARK (Ex9PB series) - Red / Green button - Rectangular bezel / 42x30mm rectangular extended - Spring-return (impulse/momentary) - 1NO+1NC contacts - Metallic alloy body / Chrome-plated bezel - IP40 - equivalent to 1200439

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Push-button
Product series / family name	Industrial controls > Pilot devices > Push-buttons (non-illuminated)
Sub-range name	Ex9PB series
Functions	Double-headed pushbutton/push-button/PB
Rated current	3mA (AC-15; at 240Vac) 1.9mA (AC-15; at 415Vac) 0.55mA (DC-13; at 125Vac) 0.27mA (DC-13; at 240Vac) 10A (Ith)
Color	Red / Green button Chrome bezel
Shape	Rectangular bezel 42x30mm rectangular extended
Rated operating voltage (Ue)	125 V 240 V 415 V
Rated insulation voltage (Ui)	415 V
Diameter	22.5mm mounting hole diameter
Operating mode	Spring-return (impulse/momentary)
Normally Open (NO) auxliary contacts	1 NO contacts

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Normally Closed (NC) auxiliary contacts	1 NC contacts
Contacts type	1NO+1NC contacts
Degree of protection	IP40
Dimensions	W42mm x D30mm bezel H55mm x W42mm x D30mm H2.17" x W1.65" x D1.18"
Material	Metallic alloy body Chrome-plated bezel
Order code / Manufacturer SKU	Ex9PBL8425 1200439
Manufacturer product status	Commercialized
Equivalent to	1200439
Compliant with standard(s)	UL Listed (File Number E353865) CSA IEC/EN 60947 VDE 0660 CE compliant RoHS compliant

Benefits

Features
- Metal construction for superior durability and visual appeal
- UL recognized component and labeled IP 40 (front) for protection against dust and water
- Low behind the panel depth
- Operators mount in a round 7/8 in (22.5 mm) hole that is interchangeable with competitor's products
- Field convertible from maintained to momentary (available on maintained pushbuttons only)
- More than one million mechanical operations on momentary and half million on maintained pushbuttons

Documents

E-PLAN - NOARK - Ex9PBL8425 - Part details

NOARK - 22mm Pilot Devices - Datasheet.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com