

NOARK

# Ex9PBS444

Push-button - Ex9PB - 1200451 - Twist-to-release - 30mm mushroom head - Red - 2NC

Pushbutton/push-button/PB - NOARK (Ex9PB series) - Red button - Round bezel / diam. 30mm mushroom head - Push-on / Twisted-OFF / Twist-to-release - 2NC contacts - Metallic alloy body / Chrome-plated bezel - IP40 - equivalent to 1200451

## Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

## Specifications

| | |
|---|---|
| **Primary brand** | NOARK |
| **Main function** | Push-button |
| **Product series / family name** | Industrial controls > Pilot devices > Push-buttons (non-illuminated) |
| **Sub-range name** | Ex9PB series |
| **Functions** | Pushbutton/push-button/PB |
| **Rated current** | 3mA (AC-15; at 240Vac)<br>1.9mA (AC-15; at 415Vac)<br>0.55mA (DC-13; at 125Vac)<br>0.27mA (DC-13; at 240Vac)<br>10A (Ith) |
| **Color** | Red button<br>Chrome bezel |
| **Shape** | Round bezel<br>diam. 30mm mushroom head |
| **Rated operating voltage (Ue)** | 125 V<br>240 V<br>415 V |
| **Rated insulation voltage (Ui)** | 415 V |
| **Diameter** | 22.5mm mounting hole diameter |
| **Operating mode** | Push-on / Twisted-OFF / Twist-to-release |
| **Normally Open (NO) auxliary contacts** | 0 NO contacts |

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

| | |
|---|---|
| **Normally Closed (NC) auxiliary contacts** | 2 NC contacts |
| **Contacts type** | 2NC contacts |
| **Degree of protection** | IP40 |
| **Dimensions** | H77mm x W40mm x D30mm<br>H3.03" x W1.57" x D1.18" |
| **Material** | Metallic alloy body<br>Chrome-plated bezel |
| **Order code / Manufacturer SKU** | Ex9PBS444<br>1200451 |
| **Manufacturer product status** | Commercialized |
| **Equivalent to** | 1200451 |
| **Compliant with standard(s)** | UL Listed (File Number E353865)<br>CSA<br>IEC/EN 60947<br>VDE 0660<br>CE compliant<br>RoHS compliant |

## Benefits

Features
- Metal construction for superior durability and visual appeal
- UL recognized component and labeled IP 40 (front) for protection against dust and water
- Low behind the panel depth
- Operators mount in a round 7/8 in (22.5 mm) hole that is interchangeable with competitor's products
- Field convertible from maintained to momentary (available on maintained pushbuttons only)
- More than one million mechanical operations on momentary and half million on maintained pushbuttons

## Documents

E-PLAN - NOARK - Ex9PBS444 - Part details

NOARK - 22mm Pilot Devices - Datasheet.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com