

NOARK

Ex9PBS541

Push-button - Ex9PB - 1200453 - Twist-to-release - 40mm mushroom head - Red - 1NO

Pushbutton/push-button/PB - NOARK (Ex9PB series) - Red button - Round bezel / diam. 40mm mushroom head - Push-on / Twisted-OFF / Twist-to-release - 1NO contact - Metallic alloy body / Chrome-plated bezel - IP40 - equivalent to 1200453

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Push-button
Product series / family name	Industrial controls > Pilot devices > Push-buttons (non-illuminated)
Sub-range name	Ex9PB series
Functions	Pushbutton/push-button/PB
Rated current	3mA (AC-15; at 240Vac) 1.9mA (AC-15; at 415Vac) 0.55mA (DC-13; at 125Vac) 0.27mA (DC-13; at 240Vac) 10A (Ith)
Color	Red button Chrome bezel
Shape	Round bezel diam. 40mm mushroom head
Rated operating voltage (Ue)	125 V 240 V 415 V
Rated insulation voltage (Ui)	415 V
Diameter	22.5mm mounting hole diameter
Operating mode	Push-on / Twisted-OFF / Twist-to-release
Normally Open (NO) auxliary contacts	1 NO contacts

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Normally Closed (NC) auxiliary contacts	0 NC contacts
Contacts type	1NO contact
Degree of protection	IP40
Dimensions	H77mm x W40mm x D40mm H3.03" x W1.57" x D1.57"
Material	Metallic alloy body Chrome-plated bezel
Order code / Manufacturer SKU	Ex9PBS541 1200453
Manufacturer product status	Commercialized
Equivalent to	1200453
Compliant with standard(s)	UL Listed (File Number E353865) CSA IEC/EN 60947 VDE 0660 CE compliant RoHS compliant

Benefits

Features
- Metal construction for superior durability and visual appeal
- UL recognized component and labeled IP 40 (front) for protection against dust and water
- Low behind the panel depth
- Operators mount in a round 7/8 in (22.5 mm) hole that is interchangeable with competitor's products
- Field convertible from maintained to momentary (available on maintained pushbuttons only)
- More than one million mechanical operations on momentary and half million on maintained pushbuttons

Documents

E-PLAN - NOARK - Ex9PBS541 - Part details

NOARK - 22mm Pilot Devices - Datasheet.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com