

NOARK

# Ex9PBW3464N

Illuminated push-button - Ex9PB - 1200300 - Momentary - Round Flat - w/guard - Red - 2NC - 110Vac/dc LED

Illuminated pushbutton/push-button/PB with LED + guard - full-voltage input - NOARK (Ex9PB series) - Red - Round bezel / 22mm (7/8") round flat / flush - Spring-return (impulse/momentary) - 2NC contacts - Metallic alloy body / Chrome-plated bezel - Supply voltage 110Vac / 110Vdc - IP40 - equivalent to 1200300

## Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

## Specifications

| | |
|---|---|
| **Primary brand** | NOARK |
| **Main function** | Push-button (Illuminated) |
| **Product series / family name** | Industrial controls > Pilot devices > Push-buttons (illuminated) |
| **Sub-range name** | Ex9PB series |
| **Functions** | Illuminated pushbutton/push-button/PB |
| **Design** | LED<br>guard<br>full-voltage input |
| **Supply voltage (AC)** | 110Vac |
| **Supply voltage (DC)** | 110Vdc |
| **Rated current** | 3mA (AC-15; at 240Vac)<br>1.9mA (AC-15; at 415Vac)<br>0.55mA (DC-13; at 125Vac)<br>0.27mA (DC-13; at 240Vac)<br>10A (Ith) |
| **Light Color** | Red |
| **Color** | Chrome bezel |
| **Shape** | Round bezel<br>22mm (7/8") round flat / flush |
| **Rated insulation voltage (Ui)** | 415 V |

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

| | |
|---|---|
| **Diameter** | 22.5mm mounting hole diameter |
| **Operating mode** | Spring-return (impulse/momentary) |
| **Normally Open (NO) auxliary contacts** | 0 NO contacts |
| **Normally Closed (NC) auxiliary contacts** | 2 NC contacts |
| **Contacts type** | 2NC contacts |
| **Degree of protection** | IP40 |
| **Dimensions** | H80mm x W40mm x D30mm<br>H3.27" x W1.57" x D1.18" |
| **Material** | Metallic alloy body<br>Chrome-plated bezel |
| **Current consumption** | 20mA max. |
| **Order code / Manufacturer SKU** | Ex9PBW3464N<br>1200300 |
| **Manufacturer product status** | Commercialized |
| **Equivalent to** | 1200300 |
| **Compliant with standard(s)** | UL Listed (File Number E353865)<br>CSA<br>IEC/EN 60947<br>VDE 0660<br>CE compliant<br>RoHS compliant |

## Benefits

Features
- Metal construction for superior durability and visual appeal
- UL recognized component and labeled IP 40 (front) for protection against dust and water
- Low behind the panel depth
- Operators mount in a round 7/8 in (22.5 mm) hole that is interchangeable with competitor's products
- Field convertible from maintained to momentary (available on maintained pushbuttons only)
- More than one million mechanical operations on momentary and half million on maintained pushbuttons

## Documents

NOARK - 22mm Pilot Devices - Datasheet.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com