

NOARK

Ex9PBW3664F

Illuminated push-button - Ex9PB - 1200297 - Momentary - Round Flat - w/guard - Blue - 2NC - 48Vac/dc LED

Illuminated pushbutton/push-button/PB with LED + guard - full-voltage input - NOARK (Ex9PB series) - Blue - Round bezel / 22mm (7/8") round flat / flush - Spring-return (impulse/momentary) - 2NC contacts - Metallic alloy body / Chrome-plated bezel - Supply voltage 48Vac / 48Vdc - IP40 - equivalent to 1200297

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Push-button (Illuminated)
Product series / family name	Industrial controls > Pilot devices > Push-buttons (illuminated)
Sub-range name	Ex9PB series
Functions	Illuminated pushbutton/push-button/PB
Design	LED guard full-voltage input
Supply voltage (AC)	48Vac
Supply voltage (DC)	48Vdc
Rated current	3mA (AC-15; at 240Vac) 1.9mA (AC-15; at 415Vac) 0.55mA (DC-13; at 125Vac) 0.27mA (DC-13; at 240Vac) 10A (Ith)
Light Color	Blue
Color	Chrome bezel
Shape	Round bezel 22mm (7/8") round flat / flush
Rated insulation voltage (Ui)	415 V
Diameter	22.5mm mounting hole diameter

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Operating mode	Spring-return (impulse/momentary)
Normally Open (NO) auxliary contacts	0 NO contacts
Normally Closed (NC) auxiliary contacts	2 NC contacts
Contacts type	2NC contacts
Degree of protection	IP40
Dimensions	H80mm x W40mm x D30mm H3.27" x W1.57" x D1.18"
Material	Metallic alloy body Chrome-plated bezel
Current consumption	20mA max.
Order code / Manufacturer SKU	Ex9PBW3664F 1200297
Manufacturer product status	Commercialized
Equivalent to	1200297
Compliant with standard(s)	UL Listed (File Number E353865) CSA IEC/EN 60947 VDE 0660 CE compliant RoHS compliant

Benefits

Features
- Metal construction for superior durability and visual appeal
- UL recognized component and labeled IP 40 (front) for protection against dust and water
- Low behind the panel depth
- Operators mount in a round 7/8 in (22.5 mm) hole that is interchangeable with competitor's products
- Field convertible from maintained to momentary (available on maintained pushbuttons only)
- More than one million mechanical operations on momentary and half million on maintained pushbuttons

Documents

NOARK - 22mm Pilot Devices - Datasheet.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com