

NOARK

Ex9PBW8465H

Illuminated double-headed push-button - Ex9PB - 1200447 - Momentary - Rectangular extended - Red/Green - 1NO+1NC - 230Vac/dc LED

Illuminated double-headed pushbutton/push-button/PB with LED + 1 flush green button + 1 projecting red button - full-voltage input - NOARK (Ex9PB series) - Orange - Rectangular bezel / 55x30mm rectangular flush (green button) + projecting / extended (red button) - Spring-return (impulse/momentary) - 1NO+1NC contacts - Metallic alloy body / Chrome-plated bezel - Supply voltage 230Vac / 230Vdc - IP40 - equivalent to 1200447

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Push-button (Illuminated)
Product series / family name	Industrial controls > Pilot devices > Push-buttons (illuminated)
Sub-range name	Ex9PB series
Functions	Illuminated double-headed pushbutton/push-button/PB
Design	LED 1 flush green button 1 projecting red button full-voltage input
Supply voltage (AC)	230Vac
Supply voltage (DC)	230Vdc
Rated current	3mA (AC-15; at 240Vac) 1.9mA (AC-15; at 415Vac) 0.55mA (DC-13; at 125Vac) 0.27mA (DC-13; at 240Vac) 10A (Ith)
Light Color	Orange
Color	Chrome bezel
Shape	Rectangular bezel 55x30mm rectangular flush (green button) + projecting / extended (red button)

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Rated insulation voltage (Ui)	415 V
Diameter	22.5mm mounting hole diameter
Operating mode	Spring-return (impulse/momentary)
Normally Open (NO) auxliary contacts	1 NO contacts
Normally Closed (NC) auxiliary contacts	1 NC contacts
Contacts type	1NO+1NC contacts
Degree of protection	IP40
Dimensions	W30mm x D55mm bezel H98mm x W55mm X D30mm H3.86" x W2.17" x D1.18"
Material	Metallic alloy body Chrome-plated bezel
Current consumption	20mA max.
Order code / Manufacturer SKU	Ex9PBW8465H 1200447
Manufacturer product status	Commercialized
Equivalent to	1200447
Compliant with standard(s)	UL Listed (File Number E353865) CSA IEC/EN 60947 VDE 0660 CE compliant RoHS compliant

Benefits

Features
- Metal construction for superior durability and visual appeal
- UL recognized component and labeled IP 40 (front) for protection against dust and water
- Low behind the panel depth
- Operators mount in a round 7/8 in (22.5 mm) hole that is interchangeable with competitor's products
- Field convertible from maintained to momentary (available on maintained pushbuttons only)
- More than one million mechanical operations on momentary and half million on maintained pushbuttons

Documents

NOARK - 22mm Pilot Devices - Datasheet.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com