

NOARK

Ex9R500B500A

Thermal overload relay (TOR) - 1420038 - Ex9R - 500A frame - 380-500A setting - class 10 - surface mount

Thermal overload relay (TOR) - NOARK (Ex9R series) - 380A...500A current setting range - 3-poles (3P) - 1NO+1NC (1 Normally Open + 1 Normally Closed) aux. contacts - Busb. connections (main power) + Screw-clamp connections (aux. contacts) - Surface mounting - frame size 500AF - compatible with 225-500A Ex9C devices - equivalent to 1420038

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Thermal Overload Relay (TOR)
Product series / family name	Industrial controls > Overload relays
Sub-range name	Ex9R series
Network frequency	50/60 Hz
Functions	Thermal overload relay (TOR) Automatic / manual reset function Temperature compensation Tripping indicator TEST and STOP pushbutton
Poles	3-poles (3P)
Rated current	380A...500A current setting range Contacts ratings 1.64A rated operating current (at 220Vac; AC-15; aux. contact) 0.95A rated operating current (at 380Vac; AC-15; aux. contact) 0.13A rated operating current (at 220Vdc; DC-13; aux. contact) 5A (continuous; at 600Vac; aux. contacts) 1A (continuous; at 300Vdc; aux. contacts)
Rated operating voltage (Ue)	600 V
Rated impulse voltage (Uimp)	6 kV
Connection type	Busb. connections (main power) Screw-clamp connections (aux. contacts) 11mm stripping length (aux. contact connections)

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Cross-section	#18AWG...#12AWG / 1mm2...2.5mm2 conductors (auxiliary contact terminal connection)
Short circuit breaking rating	30kA (3-phase at 600Vac)
Protection functions	Adjustable thermal protection (Overload) Class 10A Phase failure protection
Protection settings	Protection against thermal overload -- 380A...500A (adjustable) Phase failure -- 0.3 x In sensitivity
Mounting mode	Surface mounting
Contacts type	1NO+1NC (1 Normally Open + 1 Normally Closed) aux. contacts
Dimensions	frame size 500AF H5.87" x W5.71" x D5.75" H149mm x W145mm x D146mm
Technical compatibility with	225-500A Ex9C devices
Minimum current	380 A
Maximum current	500 A
Order code / Manufacturer SKU	Ex9R500B500A 1420038
Manufacturer product status	Commercialized
Equivalent to	1420038
Compliant with standard(s)	UL listed (file number E353865) UL 60947-1 UL 60947-4-1 IEC/EN 60947-4-1 cUL CE CCC CSA
Class	10
Tightening torque	(main power connection) 35 N.m (auxiliary contact connection) 1.7 N.m
Degree of pollution	III
Application type	2000m / 6562ft max. operating altitude

Benefits

- For use with Ex9C and Ex9CR
- Rated current up to 500A at 600Vac, 50/60Hz
- Overload protection trip Class 10 and Class 10A
- Phase loss sensitivity
- Adjustable current setting for overload protection
- Automatic or manual reset selectable

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

- Status indication
- STOP and TEST function
- Direct mount to contactors or 35mm DIN rail mounting base option
- 5-year limited warranty

Documents

E-PLAN - NOARK - Ex9R500B500A - Part details

NOARK - Industrial controls - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com