

NOARK

F30P1

Fuse holder - 1002606 - 1P - 1000Vdc - photovoltaic

Fuse holder - photovoltaic - 10x38mm - NOARK (F30 series) - 30A max. rated current - 1-pole (1P) - 1000Vdc rated voltage - DIN rail mounting (35mm width) - equivalent to 1002606

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Fuse holder
Product series / family name	Electrical protection > Fuse protections > Fuse-holders
Sub-range name	F30 series
Functions	Fuse holder
Design	photovoltaic - 10x38mm
Poles	1-pole (1P)
Rated current	30A max.
Rated Voltage (DC)	1000Vdc
Cross-section	for #18AWG...#6AWG / 0.75mm2...16mm2 Copper wire
Short circuit breaking rating	50kA
Mounting mode	DIN rail
Degree of protection	IP20
Dimensions	H80mm x W79mm x D17.8mm H3.15" x W3.11" x D0.7"
Net Width (mm)	35 mm
Ambient air temperature for operation	-22°F...+185°F / -30°C...+85 °C
Climatic resistance	Altitude does not exceed 6561ft (2000m)

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Order code / Manufacturer SKU	F30P1 1002606
Manufacturer product status	Commercialized
Equivalent to	1002606
Compliant with standard(s)	UL 4248-19
Tightening torque	18lb.in / 2 N.m
Degree of pollution	III

Documents

NOARK - F30 series fuse holder - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com