

NOARK

L1H463 H

RCCB UL1053 - 1003291 - 4P - 63A - 10kA - 480Vac - 22mA sensitivity - A-SI

Residual Current Circuit Breaker (RCCB) - UL1053 - A-SI protection type (Super Immune) - NOARK (L1H series) - 63A rated current - 4-poles (4P) - 10kA interrupting rating - 480Vac (UL) / 415Vac (CE) rated voltage - 22mA (UL) / 30mA (CE) residual current sensitivity - screw term. connections - DIN rail mounting (72mm width) - equivalent to 1003291 / L1H463H

Specifications

Primary brand	NOARK
Main function	Residual Current Circuit Breaker (RCCB)
Product series / family name	Electrical protection > Circuit breakers > Residual Current Circuit Breakers (RCCBs)
Sub-range name	L1H series
Functions	Residual Current Circuit Breaker (RCCB)
Design	A-SI protection type (Super Immune) Electromagnitic tripping type
Poles	4-poles (4P)
Display	Real contact position indicator Leakage fault indication window
Rated current	63A 100A gG/gL (max. admissible back-up fuse)
Residual current sensitivity	22mA (UL) 30mA (CE)
Rated voltage (AC)	480Vac (UL) 415Vac (CE)
Rated impulse voltage (Uimp)	4 kV
Connection type	screw term. connections
Short circuit breaking rating	10kA
Mounting mode	DIN rail
Dimensions	H86mm x W72mm x D79mm H3.39" x W2.83" x D3.11"
Net Width (mm)	72 mm

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Ambient air temperature for operation	-13°F...+104°F / -25°C...+40 °C
Ambient air temperature for storage	-40°F...+176°F / -40°C...+80 °C
Climatic resistance	At +68°F (+20°C) the relative humidity does not exceed 90% At +104°F (+40°C) the relative humidity does not exceed 50% Altitude does not exceed 6561ft (2000m)
Electrical durability (with load)	2000 operations
Mechanical durability (at no load)	2000 operations
GTIN code	840352788375
Order code / Manufacturer SKU	L1H463 H 1003291
Manufacturer product status	Commercialized
Equivalent to	1003291 L1H463H
Compliant with standard(s)	UL1053 RoHS compliant cULus CE IEC/EN 61008-1 CCC GB/T 16916.1
Degree of pollution	2 II

Benefits

L1H residential circuit breakers (RCCB) complies with UL 1053 standard.
It is an electrical protection device used to detect the residual current in the circuits, protect personnels from electric shocks, and prevent electrical fires.
It can be applied in devices such as charging files, enclosures, food processing equipment.

Features
- Rated voltage up to 480V
- Current withstand rating at 10kA
- Flexible wiring, arbitrary from both above and below
- Electromagnetic type leakage protection, with stable performance and strong anti-interference capability

Standards and certifications
- UL 1053
- IEC/EN 61008-1
- GB/T 16916.1

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Documents

NOARK - L1H Residential Current Circuit - Catalog.pdf

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com