NOARK

M1PVS20T3LC

DC MCCB - 1102477 - UL489B - M1 frame - 3P3d - 20A rated - lug connections+type C jumper - 1000Vdc - 10kA

DC Moulded Case Circuit Breaker (MCCB) - UL489B listed - NOARK (Ex9M1PVS series) - 3-poles (3P3d) - Rated current 20A - Interrupting capacity 10kA (at 1000Vdc) - type "C" poles jumper connection / Lugs on both load and line sides - Thermal-Magnetic (fixed) (FT/FM (Fixed Thermal / Fixed Magnetic)) trip unit - equivalent to 1102477

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Moulded Case Circuit Breaker (MCCB)
Product series / family name	Electrical protection > Circuit breakers > DC Moulded Case Circuit Breakers (MCCBs)
Sub-range name	Ex9M1PVS series
Functions	DC Moulded Case Circuit Breaker (MCCB)
Poles	3-poles (3P3d)
Rated current	20A
Trip current rating	20 AT
Frame current rating	80 AF
Rated Voltage (DC)	1000Vdc (rated service voltage)
Connection type	type "C" poles jumper connection (for both grounded and ungrounded system wirings; 3 breaker poles in series on "+" line; load connection on upper breaker pads) Lugs on both load and line sides
Short circuit breaking rating	10kA (at 1000Vdc)
Trip unit type	Technology = Thermal-Magnetic (fixed) Series = FT/FM (Fixed Thermal / Fixed Magnetic)
Protection functions	Fixed thermal protection (Overload) Fixed threshold magnetic protection (Short-circuit)

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Protection settings	Protection against thermal overload -- fixed at 20A Magnetic instantaneous protection against short-circuit -- fixed at 200A
Dimensions	H238mm x W90mm x D84.5mm H9.37" x W3.5" x D3.33"
Ambient air temperature for operation	-20˚C...+50 ˚C
Order code / Manufacturer SKU	M1PVS20T3LC 1102477
Manufacturer product status	Commercialized
Equivalent to	1102477
Compliant with standard(s)	UL489B listed UL489 listed (file number E355392) UL489B listed (file number E513573) CSA C22.2 No.5 IEC/EN 60947-2 CE marking RoHS compliant
Mechanical durability	10000 hours

Benefits

The NOARK Electric M1PVS is a UL489B DC MCCB, with current ratings of 15A to 80A, with a 10kA breaking capacity at 1000Vdc.
Each unit is equipped with thermal magnetic trip units for protection of overload and short circuit in photovoltaic system.
The M1PVS features a poles-in-series design and is equipped with pre-installed jumpers.
4 jumper connection configurations are offered for grounded and ungrounded systems.
M1PVS is backed by a 5-year limited warranty.

Documents

NOARK - MCCB MCP MCS Ex9 series-M - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com