


NOARK

# M2MS250T3L

MCP - 1101998 - UL489 - M2 frame - 3P3d - 250A rated - lug connections - 600Vac

Motor Circuit Protector (MCP) - UL489 listed - NOARK (Ex9M2M series) - 3-poles (3P3d) - Rated current 250A (continuous Amperes) - Interrupting capacity 35kA (480Vac) - Lugs on both load and line sides - Magnetic only trip unit - equivalent to 1101998

## Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

## Specifications

| | |
|---|---|
| **Primary brand** | NOARK |
| **Main function** | Motor Protection Circuit Breaker (MPCB) |
| **Product series / family name** | Electrical protection > Circuit breakers > Motor-Circuit Protectors (MCPs) |
| **Sub-range name** | Ex9M2M series |
| **Functions** | Motor Circuit Protector (MCP) |
| **Poles** | 3-poles (3P3d) |
| **Rated current** | 250A (continuous Amperes) |
| **Frame current rating** | 250 AF |
| **Rated operating voltage (Ue)** | (IEC) 690 V |
| **Rated voltage (AC)** | 600Vac (50/60Hz) |
| **Rated impulse voltage (Uimp)** | 8 kV |
| **Rated insulation voltage (Ui)** | 800 V |
| **Connection type** | Lugs on both load and line sides |
| **Short circuit breaking rating** | 50kA (240Vac)<br>35kA (480Vac)<br>14kA (600Vac) |
| **Ultimate short circuit current breaking capacity (Icu)** | 50kA (220/240Vac)<br>50kA (380/415Vac)<br>6kA (660/690Vac) |

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

| | |
|---|---|
| **Trip unit type** | Technology = Magnetic only |
| **Protection functions** | Adjustable threshold Magnetic protection (Short-circuit) |
| **Protection settings** | Magnetic instantaneous protection against short-circuit -- adjustable to 7 pre-defined settings (1250A / 1500A / 1750A / 2000A / 2250A / 2500A / 2750A) |
| **Dimensions** | H182mm x W105mm x D38mm<br>H7.17" x W4.13" x D3.47" |
| **Order code / Manufacturer SKU** | M2MS250T3L<br>1101998 |
| **Manufacturer product status** | Commercialized |
| **Equivalent to** | 1101998 |
| **Compliant with standard(s)** | UL489 listed<br>UL489 recognized (file number E355392)<br>CSA C22.2 No.5<br>IEC/EN 60947-2<br>CE marking<br>RoHS compliant |
| **Electrical durability** | 6000 hours |
| **Mechanical durability** | 10000 hours |

## Benefits

NOARK Electric offers a complete range of 3pole Molded Case Motor Circuit Protectors (MCPs magnetic only)
These MCPs are for 3-phase asynchronous motors protection.
We offer MCPs in 6 frame sizes - M1M (150A), M2M (250A), M3M (400A), M4M (600A), M5M (800A) and M6M (1200A).
Each frame size offers a range of interrupting voltage ratings from 240-690Vac.
This series MCP conforms to global standards that include UL 489 / CSA C22.2 No 5 and IEC 60947-2.
The traditional system used for this purpose relies on 3 different devices.
These include a circuit breaker, a thermal relay and a contactor for motor switching.

In particular, when selecting these devices, different factors must be taken into consideration such as
- The rated motor power
- The type of motor with cage rotor or with wound rotor
- The fault current at the point of the network where the motor is installed

Certifications
- UL 489 Recognized File Number E355392
- UL Recognized to UL489 and CSA standards 22.2 No. 5
- IEC/EN 60947-2
- CE Compliant
- RoHS Compliant

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

## Documents

E-PLAN - NOARK - M2MS250T3L - Part details

NOARK - MCCB MCP MCS Ex9 series-M - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com