

NOARK

M2N225T22

MCCB - 1102349 - UL489 - M2 frame - 2P2d - 225A rated - busbar connections - 600Vac

Moulded Case Circuit Breaker (MCCB) - UL489 listed - NOARK (Ex9M2 series) - 2-poles (2P2d) - Rated current 225A - Interrupting capacity 65kA (480Vac) - Term. nut kit (for fixed busb. connection) on both line and load sides - Thermal-Magnetic (adjustable) (AT/AM (Adjustable Thermal / Adjustable Magnetic)) trip unit - equivalent to 1102349

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Moulded Case Circuit Breaker (MCCB)
Product series / family name	Electrical protection > Circuit breakers > AC Moulded Case Circuit Breakers (MCCBs)
Sub-range name	Ex9M2 series
Functions	Moulded Case Circuit Breaker (MCCB)
Poles	2-poles (2P2d)
Rated current	225A
Trip current rating	225 AT
Frame current rating	250 AF
Rated operating voltage (Ue)	(IEC) 690 V
Rated voltage (AC)	600Vac
Rated impulse voltage (Uimp)	8 kV
Rated insulation voltage (Ui)	800 V
Connection type	Term. nut kit (for fixed busb. connection) on both line and load sides
Cross-section	connects with #8AWG...350kcmil / 10mm2...185mm2 conductors

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Short circuit breaking rating	100kA (240Vac) 65kA (480Vac) 20kA (600Vac) 35kA (500Vdc)
Ultimate short circuit current breaking capacity (Icu)	100kA (220/240Vac) 100kA (380/415Vac) 10kA (660/690Vac)
Trip unit type	Technology = Thermal-Magnetic (adjustable) Series = AT/AM (Adjustable Thermal / Adjustable Magnetic)
Protection functions	Adjustable thermal protection (Overload) Adjustable threshold magnetic protection (Short-circuit)
Protection settings	Protection against thermal overload -- adjustable 0.8...1 x In (180A...225A) Magnetic instantaneous protection against short-circuit -- adjustable 5...10 x In (1125A...2250A)
Dimensions	H182mm x W75mm x D88mm H7.17" x W2.95" x D3.47"
Ambient air temperature for operation	-25˚C...+70 ˚C
Utilisation category	A
Order code / Manufacturer SKU	M2N225T22 1102349
Manufacturer product status	Commercialized
Equivalent to	1102349
Compliant with standard(s)	UL489 listed UL489 listed (file number E355392) CSA C22.2 No.5 IEC/EN 60947-2 CE marking RoHS compliant
Electrical durability	6000 hours
Mechanical durability	10000 hours

Benefits

Ex9M series offers
- High-breaking capacity and a patented arc extinguishing design
- Bearing-type spindle reduces the operating force required to open and close the operating mechanism
- High quality compact modular design
- Fixed and adjustable trip unit settings
- Line and load lugs installed standard
- 5-Year limited warranty

Certifications
- UL 489 listed File Number E355392

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

- UL listed to UL489 and Canada CSA standards 22.2 No. 5
- IEC/EN 60947-2
- CE Compliant
- UL489B, File Number E513573

Wide range of accessories
- Alarm switch and auxiliary contact
- Shunt and undervoltage trip
- Rotary type handle
- Flange type handle
- Motor Operator
- Mechanical Interlock

Documents

NOARK - MCCB MCP MCS Ex9 series-M - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com