

NOARK

M3HVN300T3

MCCB - 1103255 - UL489 - 3P3d - 300A rated - busbar connections - 800Vac

Moulded Case Circuit Breaker (MCCB) - UL489 listed - NOARK (Ex9M3HV series) - 3-poles (3P3d) - Rated current 300A - Interrupting capacity 50kA (800Vac) - busb. connections - Thermal-Magnetic (adjustable) (AT/AM (Adjustable Thermal / Adjustable Magnetic)) trip unit - equivalent to 1103255

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Moulded Case Circuit Breaker (MCCB)
Product series / family name	Electrical protection > Circuit breakers > AC Moulded Case Circuit Breakers (MCCBs)
Sub-range name	Ex9M3HV series
Functions	Moulded Case Circuit Breaker (MCCB)
Poles	3-poles (3P3d)
Rated current	300A
Trip current rating	300 AT
Frame current rating	400 AF
Rated voltage (AC)	800vac
Connection type	busb. connections
Short circuit breaking rating	50kA (800Vac) 85kA (600Vac)
Trip unit type	Technology = Thermal-Magnetic (adjustable) Series = AT/AM (Adjustable Thermal / Adjustable Magnetic)
Protection functions	Adjustable thermal protection (Overload) Adjustable threshold magnetic protection (Short-circuit)
Protection settings	Protection against thermal overload -- adjustable 0.7...1 x In (210A...300A) Magnetic instantaneous protection against short-circuit -- adjustable 5...10 x In (1500A...3000A)

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Dimensions	H400mm x W140mm x D187.5mm H15.75" x W5.5" x D7.38"
Order code / Manufacturer SKU	M3HVN300T3 1103255
Manufacturer product status	Commercialized
Equivalent to	1103255
Compliant with standard(s)	UL489 listed cULus listed

Documents

NOARK - UL 800VAC MCCB - M2HV M3HV - Datasheet.pdf

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com