

NOARK

M3S250EN4L

MCCB - 1103378 - Electronic (LSI) - UL489 - 4P4d - 250A rated - lug connections - 600Vac - EN DIP sw. trip unit

Moulded Case Circuit Breaker (MCCB) with EN DIP sw. trip unit - UL489 listed - NOARK (Ex9M3E series) - 4-poles (4P4d) - Rated current 250A - Interrupting capacity 42kA (480Vac) - Lugs on both load and line sides - Electronic (Series 3.0 (LSI)) trip unit - equivalent to 1103378

Specifications

Primary brand	NOARK
Main function	Moulded Case Circuit Breaker (MCCB)
Product series / family name	Electrical protection > Circuit breakers > AC Moulded Case Circuit Breakers (MCCBs)
Sub-range name	Ex9M3E series
Functions	Moulded Case Circuit Breaker (MCCB)
Design	EN DIP sw. trip unit
Poles	4-poles (4P4d)
Frequency	50/60Hz
Rated current	250A
Trip current rating	250 AT
Frame current rating	400 AF
Rated voltage (AC)	600Vac
Rated impulse voltage (Uimp)	8 kV
Rated insulation voltage (Ui)	800 V
Connection type	Lugs on both load and line sides
Short circuit breaking rating	65kA (240Vac) 42kA (480Vac) 18kA (600Vac)
Trip unit type	Technology = Electronic Series = Series 3.0 (LSI) Protection = LSI

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Protection functions	L (Long-time protection) S (Short-time protection with fixed time delay) I (Instantaneous protection)
Protection settings	L - Protection against overload -- adjustable OFF/0.4/0.5/0.6/0.7/0.8/0.9/1 x In (100A...250A) (with 3...18s adjustable time setting at 6 x Ir) S - Protection against short-circuit with time delay -- adjustable OFF/1.5/2/3/4/6/8/10 x Ir (375A...2500A) (0.1...0.4s time delay) I - Instantaneous protection against short-circuit -- adjustable OFF/2/3/4/6/8/10/12 x In (500A...3000A)
Dimensions	H285mm x W185mm x D126mm
Ambient air temperature for operation	-40˚C...+70 ˚C
Utilisation category	B
Order code / Manufacturer SKU	M3S250EN4L 1103378
Manufacturer product status	Commercialized
Equivalent to	1103378
Compliant with standard(s)	UL489 listed UL GB/T 14048.2 IEC/EN 60947-2 CE marking CCC
Electrical durability	1000 hours
Mechanical durability	8000 hours

Benefits

Features
- Compliant with UL489, GB/T 14048.2, IEC/EN 60947-2 standards, with UL, CCC, and CE certifications.
- Equipped with an electronic trip unit (EN Dip Switch / EM LCD), featuring a variety of protective characteristics to adapt to different working conditions.
- Rated working voltage covers AC 240/480/600V, with a rated insulation voltage of 800V, and diverse breaking capacities.
- Suitable for continuous operation at 100%.
- A variety of accessories are available, such as auxiliary alarm switch, shunt trip, under-voltage trip, and motor operator, to meet different requirements.

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com