

NOARK

M3S250T2

MCCB - 1100306 - UL489 - M3 frame - 3P2d - 250A rated - busbar connections - 500Vdc/ac

Moulded Case Circuit Breaker (MCCB) - UL489 listed - NOARK (Ex9M3 series) - 2-poles in 3-poles case (3P2d) - Rated current 250A - Interrupting capacity 42kA (480Vac) - Term. nut kit (for fixed busb. connection) on both line and load sides - Thermal-Magnetic (adjustable) (AT/AM (Adjustable Thermal / Adjustable Magnetic)) trip unit - equivalent to 1100306

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Moulded Case Circuit Breaker (MCCB)
Product series / family name	Electrical protection > Circuit breakers > AC Moulded Case Circuit Breakers (MCCBs)
Sub-range name	Ex9M3 series
Functions	Moulded Case Circuit Breaker (MCCB)
Poles	2-poles in 3-poles case (3P2d)
Rated current	250A
Trip current rating	250 AT
Frame current rating	400 AF
Rated operating voltage (Ue)	(IEC) 690 V
Rated Voltage (DC)	500Vdc
Rated voltage (AC)	600Vac
Rated impulse voltage (Uimp)	8 kV
Rated insulation voltage (Ui)	800 V
Connection type	Term. nut kit (for fixed busb. connection) on both line and load sides

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Cross-section	connects with #3/0AWG (000)...500kcmil / 95mm2...240mm2 conductors (1-hole lugs) or #3AWG...250kcmil / 35mm2...120mm2 conductors (2-hole lugs)
Short circuit breaking rating	65kA (240Vac) 42kA (480Vac) 18kA (600Vac) 35kA (500Vdc)
Ultimate short circuit current breaking capacity (Icu)	65kA (220/240Vac) 65kA (380/415Vac) 10kA (660/690Vac) 35kA (500Vdc)
Trip unit type	Technology = Thermal-Magnetic (adjustable) Series = AT/AM (Adjustable Thermal / Adjustable Magnetic)
Protection functions	Adjustable thermal protection (Overload) Adjustable threshold magnetic protection (Short-circuit)
Protection settings	Protection against thermal overload -- adjustable 0.8...1 x In (200A...250A) Magnetic instantaneous protection against short-circuit -- adjustable 5...10 x In (1250A...2500A)
Dimensions	H285mm x W140mm x D116.5mm H11.22" x W5.51" x D4.59"
Ambient air temperature for operation	-25˚C...+70 ˚C
Utilisation category	A
Order code / Manufacturer SKU	M3S250T2 1100306
Manufacturer product status	Commercialized
Equivalent to	1100306
Compliant with standard(s)	UL489 listed UL489 listed (file number E355392) CSA C22.2 No.5 IEC/EN 60947-2 CE marking RoHS compliant
Electrical durability	5000 hours
Mechanical durability	8000 hours

Benefits

Ex9M series offers
- High-breaking capacity and a patented arc extinguishing design
- Bearing-type spindle reduces the operating force required to open and close the operating mechanism
- High quality compact modular design
- Fixed and adjustable trip unit settings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

- Line and load lugs installed standard
- 5-Year limited warranty

Certifications
- UL 489 listed File Number E355392
- UL listed to UL489 and Canada CSA standards 22.2 No. 5
- IEC/EN 60947-2
- CE Compliant
- UL489B, File Number E513573

Wide range of accessories
- Alarm switch and auxiliary contact
- Shunt and undervoltage trip
- Rotary type handle
- Flange type handle
- Motor Operator
- Mechanical Interlock

Documents

NOARK - MCCB MCP MCS Ex9 series-M - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com