NOARK

M5S700T4C

MCCB - 1102056 - UL489 - M5 frame - 4P4d - 700A rated - busbar connections - 600Vdc/ac - 100% neutral

Moulded Case Circuit Breaker (MCCB) - UL489 listed - NOARK (Ex9M5 series) - 4-poles (4P4d) - Rated current 700A - 100% neutral - Interrupting capacity 42kA (480Vac) - Term. nut kit (for fixed busb. connection) on both line and load sides - Thermal-Magnetic (adjustable) (AT/AM (Adjustable Thermal / Adjustable Magnetic)) trip unit - equivalent to 1102056

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Moulded Case Circuit Breaker (MCCB)
Product series / family name	Electrical protection > Circuit breakers > AC Moulded Case Circuit Breakers (MCCBs)
Sub-range name	Ex9M5 series
Functions	Moulded Case Circuit Breaker (MCCB)
Poles	4-poles (4P4d)
Rated current	700A
Trip current rating	700 AT
Frame current rating	800 AF
Rated operating voltage (Ue)	(IEC) 690 V
Rated Voltage (DC)	600Vdc
Rated voltage (AC)	600Vac
Rated impulse voltage (Uimp)	8 kV
Rated insulation voltage (Ui)	800 V
Connection type	Term. nut kit (for fixed busb. connection) on both line and load sides

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Cross-section	connects with 250kcmil...600kcmil / 120mm2...300mm2 conductors (2-hole lugs) or 250kcmil...500kcmil / 100mm2...250mm2 conductors (3-hole lugs)
Short circuit breaking rating	65kA (240Vac) 42kA (480Vac) 22kA (600Vac) 35kA (600Vdc)
Ultimate short circuit current breaking capacity (Icu)	65kA (220/240Vac) 65kA (380/415Vac) 12kA (660/690Vac) 35kA (500Vdc)
Trip unit type	Technology = Thermal-Magnetic (adjustable) Series = AT/AM (Adjustable Thermal / Adjustable Magnetic)
Protection functions	100% neutral Adjustable thermal protection (Overload) Adjustable threshold magnetic protection (Short-circuit)
Protection settings	Protection against thermal overload -- adjustable 0.8...1 x In (560A...700A) Magnetic instantaneous protection against short-circuit -- adjustable 5...10 x In (3500A...7000A)
Dimensions	H411mm x W260mm x D192.5mm H16.18" x W10.2" x D7.58"
Ambient air temperature for operation	-25˚C...+70 ˚C
Utilisation category	A
Order code / Manufacturer SKU	M5S700T4C 1102056
Manufacturer product status	Commercialized
Equivalent to	1102056
Compliant with standard(s)	UL489 listed UL489 listed (file number E355392) CSA C22.2 No.5 IEC/EN 60947-2 CE marking RoHS compliant
Electrical durability	500 hours
Mechanical durability	3000 hours

Benefits

Ex9M series offers
- High-breaking capacity and a patented arc extinguishing design
- Bearing-type spindle reduces the operating force required to open and close the operating mechanism
- High quality compact modular design

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

- Fixed and adjustable trip unit settings
- Line and load lugs installed standard
- 5-Year limited warranty

Certifications
- UL 489 listed File Number E355392
- UL listed to UL489 and Canada CSA standards 22.2 No. 5
- IEC/EN 60947-2
- CE Compliant
- UL489B, File Number E513573

Wide range of accessories
- Alarm switch and auxiliary contact
- Shunt and undervoltage trip
- Rotary type handle
- Flange type handle
- Motor Operator
- Mechanical Interlock

Documents

NOARK - MCCB MCP MCS Ex9 series-M - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com