NOARK

M6MN1200E4L

MCP - 1101894 - 80% rated - UL489 - M6 frame - 4P4d - 1200A rated - lug connections - 600Vac

Motor Circuit Protector (MCP) - 80% rated - UL489 listed - NOARK (Ex9M6M series) - 4-poles (4P4d) - Rated current 1200A (continuous Amperes) - Interrupting capacity 65kA (480Vac) - Lugs on both load and line sides - Electronic trip unit - equivalent to 1101894

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Motor Protection Circuit Breaker (MPCB)
Product series / family name	Electrical protection > Circuit breakers > Motor-Circuit Protectors (MCPs)
Sub-range name	Ex9M6M series
Functions	Motor Circuit Protector (MCP)
Design	80% rated
Poles	4-poles (4P4d)
Rated current	1200A (continuous Amperes)
Frame current rating	1200 AF
Rated operating voltage (Ue)	(IEC) 690 V
Rated voltage (AC)	600Vac (50/60Hz)
Rated impulse voltage (Uimp)	8 kV
Rated insulation voltage (Ui)	800 V
Connection type	Lugs on both load and line sides
Short circuit breaking rating	100kA (240Vac) 65kA (480Vac) 42kA (600Vac)

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Ultimate short circuit current breaking capacity (Icu)	85kA (220/240Vac) 45kA (380/415Vac) 30kA (660/690Vac)
Trip unit type	Technology = Electronic
Protection functions	Adjustable threshold Magnetic protection (Short-circuit)
Protection settings	I - Instantaneous protection against short-circuit -- adjustable at 2/3/4/6/8/10/12 x In (6000A...13200A)
Dimensions	H575.1mm x W320mm x D385.1mm H22.64" x W12.6" x D15.16"
Order code / Manufacturer SKU	M6MN1200E4L 1101894
Manufacturer product status	Commercialized
Equivalent to	1101894
Compliant with standard(s)	UL489 listed UL489 recognized (file number E355392) CSA C22.2 No.5 IEC/EN 60947-2 CE marking RoHS compliant
Electrical durability	500 hours
Mechanical durability	3000 hours

Benefits

NOARK Electric offers a complete range of 3pole Molded Case Motor Circuit Protectors (MCPs magnetic only)
These MCPs are for 3-phase asynchronous motors protection.
We offer MCPs in 6 frame sizes - M1M (150A), M2M (250A), M3M (400A), M4M (600A), M5M (800A) and M6M (1200A).
Each frame size offers a range of interrupting voltage ratings from 240-690Vac.
This series MCP conforms to global standards that include UL 489 / CSA C22.2 No 5 and IEC 60947-2.
The traditional system used for this purpose relies on 3 different devices.
These include a circuit breaker, a thermal relay and a contactor for motor switching.

In particular, when selecting these devices, different factors must be taken into consideration such as
- The rated motor power
- The type of motor with cage rotor or with wound rotor
- The fault current at the point of the network where the motor is installed

Certifications
- UL 489 Recognized File Number E355392
- UL Recognized to UL489 and CSA standards 22.2 No. 5
- IEC/EN 60947-2
- CE Compliant

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

- RoHS Compliant

Documents

NOARK - MCCB MCP MCS Ex9 series-M - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com