


NOARK

# RDSD4HV11W600

Rotary switch-disconnector - 1600218 - UL98B - 2P - inter-pole mechanism - 600A rated - front fixed connection - 1500Vdc - IP20

Fixed-type front-operated rotary switch-disconnector - UL98B - NOARK (RDSD series) - 2-poles (2P / inter-pole mechanism) - Rated current 600A - Front fixed-type connection pads - IP20 - 600A frame - equivalent to 1600218

## Specifications

| | |
|---|---|
| **Primary brand** | NOARK |
| **Main function** | Switch-disconnector |
| **Product series / family name** | Electrical protection > Disconnector switches > DC rotary switch-disconnectors |
| **Sub-range name** | RDSD series |
| **Functions** | Fixed-type front-operated rotary switch-disconnector |
| **Design** | 600A frame |
| **Poles** | 2-poles (2P / inter-pole mechanism) |
| **Rated current** | 600A |
| **Rated Voltage (DC)** | 1500Vdc |
| **Rated impulse voltage (Uimp)** | (UL; IEC) 12 kV |
| **Rated insulation voltage (Ui)** | 1500 V |
| **Connection type** | Front fixed-type connection pads |
| **Cross-section** | connects with 225mm2...387mm2 conductors (UL)<br>connects with 185mm2...370mm2 conductors (IEC) |
| **Short circuit breaking rating** | 10kA |
| **Degree of protection** | IP20 |
| **Dimensions** | H210mm x W164mm x D137mm<br>H8.27" x W6.46" x D5.39" |
| **Ambient air temperature for operation** | -40˚C...+70 ˚C |
| **Order code / Manufacturer SKU** | RDSD4HV11W600<br>1600218 |

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

# RDSD4HV11W600

Rotary switch-disconnector - 1600218 - UL98B - 2P - inter-pole mechanism - 600A rated - front fixed connection - 1500Vdc - IP20

| | |
|---|---|
| **Manufacturer product status** | Commercialized |
| **Equivalent to** | 1600218 |
| **Compliant with standard(s)** | UL98B<br>UL<br>GB/T 14048.3<br>IEC/EN 60947-3<br>CE marking<br>CCC<br>TUV<br>RoHS compliant |
| **Electrical durability** | (UL) 400 hours<br>(IEC) 200 hours |
| **Mechanical durability** | 8000 hours |
| **Tightening torque** | (main) 25-30 N.m<br>(operating) 8-13 N.m |

## Benefits

RDSD HV Series DC Rotary Disconnect Switches

Product Overview
The Noark RDSD HV rotary disconnect switch is strictly designed and manufactured in accordance with relevant UL standards, specifically providing a safe and reliable circuit control solution for DC power systems.
This product is suitable for harsh working conditions with a maximum DC voltage of DV 1500V and a rated current of up to 1000A.
It realizes the functions of infrequent manual disconnection of the circuit and power isolation through a rotary operating mechanism.
Its core advantage lies in its ability to form an obvious physical disconnection point in line with safety regulations in the power system, providing reliable power - off protection for equipment maintenance and overhaul, and effectively reducing operational risks.
As an ideal component for high - voltage DC systems, the RDSD HV series of disconnect switch is particularly recommended for use in the photovoltaic energy storage industry, such as key nodes like the DC side of energy storage converters and the DC bus of photovoltaic inverters, providing dual protection for the reliable operation of equipment and the safe operation of personnel.

Approvals
- Standards UL 98B, IEC 60947-1/3, GB/T 14048.1/3
- Certifications UL, CE, TUV, RoHS, CCC

Features
- UL Certified Rated for 100-1000A (up to DC 1500V) with stringent temperature rise requirements.
- Wide Operating Range -40˚C to +70˚C (no derating below 70˚C).
- Flexible Installation Front or side operation options
- Mounting orientation unrestricted.
- Compact Design Series-connected poles enable high-current interruption in minimal space.

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com