

NOARK

AX4420UL

Auxiliary contact - 1330209 - Ex9C - mounts on 115A-500A cont. - 2NO

Auxiliary contact block / switch block - mounts on 115A-500A cont. - NOARK (Ex9C series) - 2NO (2 Normally Open) aux. contacts - Lift term. connection - side mounting - IP20 - equivalent to 1330209

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Auxiliary contact
Product series / family name	Industrial controls > Contactors > Standard contactors > Accessories > Auxiliary contacts
Sub-range name	Ex9C series
Functions	Auxiliary contact block / switch block
Design	mounts on 115A-500A cont.
Rated current	6A (24Vac; AC-15) 3.13A (230Vac; AC-15) 1.8A (400Vac; AC-15) 1.04A (690Vac; AC-15) 0.55A (125Vdc; DC-13) 0.27A (250Vdc; DC-13) 10A (Ith conventional free air thermal current)
Rated power	720VA (AC-15) switching 69W (DC-13) switching
Rated impulse voltage (Uimp)	6 kV
Rated insulation voltage (Ui)	690 V
Connection type	Lift term. connection
Cross-section	for #18AWG...#12AWG / 1mm2...4mm2 conductors
Mounting mode	side mounting
Normally Open (NO) auxliary contacts	2 NO contacts

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Normally Closed (NC) auxiliary contacts	0 NC contacts
Contacts type	2NO (2 Normally Open) aux. contacts
Degree of protection	IP20
Dimensions	H64mm x W10mm x D68mm H2.52" x W0.39" x D2.68"
Order code / Manufacturer SKU	AX4420UL 1330209
Manufacturer product status	Commercialized
Equivalent to	1330209
Compliant with standard(s)	UL 508 (file number E353866) IEC 60947-5-1 EN 60947-5-1 CSA CCC RoHS compliant
Tightening torque	1.7 N.m

Documents

E-PLAN - NOARK - AX4420UL - Part details

NOARK - Industrial controls - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com