

NOARK

SHT22NE

Shunt trip release coil - 1100517 - 24Vdc

Shunt trip release coil - for M2 / M3 frame size - NOARK - 24Vdc control voltage - equivalent to 1100517

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Coil (Tripping)
Product series / family name	Electrical protection > MCCBs and disconnector switches accessories > Auxiliary controls
Functions	Shunt trip release coil
Control Voltage (DC)	24Vdc 16.8-26.4Vdc (pick-up voltage)
Response time	(operating time) 10-60ms / 0.01-0.06 s
Dimensions	H46.5mm x W36.8mm x D32mm H1.83" x W1.45" x D1.26"
Technical compatibility with	for M2 / M3 frame size
Order code / Manufacturer SKU	SHT22NE 1100517
Manufacturer product status	Commercialized
Equivalent to	1100517
Compliant with standard(s)	UL489 listed (file number E355392) CSA C22.2 No.5 IEC/EN 60947-2 CE marking RoHS compliant

Documents

NOARK - MCCB MCP MCS Ex9 series-M - Catalog.pdf

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

SHT22NE

Shunt trip release coil - 1100517 - 24Vdc

Access to all NOARK drawings

E-PLAN - NOARK - SHT22NE - Part details

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com