

NOARK

SHT3101UD

Shunt trip coil UL1077 - 1002573 - 1NC - 6-12Vac/dc

Shunt trip release coil - for UL1077 devices - NOARK - 6Vac-12Vac / 6Vdc-12Vdc control voltage - 1NC (1 Normally Closed) aux. contacts - DIN rail mounting (35mm width) - equivalent to 1002573

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Coil (Tripping)
Product series / family name	Electrical protection > MCBs accessories > UL1077 > Trip coils > Shunt trip
Functions	Shunt trip release coil
Design	for UL1077 devices
Cross-section	for #18AWG...#14AWG / 0.5mm2...4mm2 Cu wires at 140/167°F / 60/75°C
Control Voltage (AC)	6Vac-12Vac
Control Voltage (DC)	6Vdc-12Vdc
Mounting mode	DIN rail
Normally Closed (NC) auxiliary contacts	1 NC contacts
Contacts type	1NC (1 Normally Closed) aux. contacts
Dimensions	H83.1mm x W17.8mm x D75.4mm 7mm / 0.3" reference stripping length H3.27" x W0.7" x D2.97"
Net Width (mm)	35 mm
Order code / Manufacturer SKU	SHT3101UD 1002573
Manufacturer product status	Commercialized
Equivalent to	1002573

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Compliant with standard(s)	UL 1077
Tightening torque	9lb.in / 1 N.m

Documents

NOARK - DIN Rail Miniature Circuit Breakers - Ex9 B1 series - Datasheet.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com