

NOARK

SHT3111LB

Shunt trip coil UL1077 - 1002609 - 1NO+1NC - 24-48Vac/dc

Shunt trip release coil - for 80-125A rated current UL1077 devices - NOARK - 24Vac-48Vac / 24Vdc-48Vdc control voltage - 1NO+1NC (1 Normally Open + 1 Normally Closed) aux. contacts - DIN rail mounting (35mm width) - equivalent to 1002609

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Coil (Tripping)
Product series / family name	Electrical protection > MCBs accessories > UL1077 > Trip coils > Shunt trip
Functions	Shunt trip release coil
Design	for 80-125A rated current UL1077 devices
Control Voltage (AC)	24Vac-48Vac
Control Voltage (DC)	24Vdc-48Vdc
Mounting mode	DIN rail
Normally Open (NO) auxliary contacts	1 NO contacts
Normally Closed (NC) auxiliary contacts	1 NC contacts
Contacts type	1NO+1NC (1 Normally Open + 1 Normally Closed) aux. contacts
Dimensions	H81.3mm x W17.8mm x D76.2mm H3.2" x W0.7" x D3"
Net Width (mm)	35 mm
Order code / Manufacturer SKU	SHT3111LB 1002609
Manufacturer product status	Commercialized

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Equivalent to	1002609
Compliant with standard(s)	UL 1077

Documents

NOARK - Essential components catalog (circuit protection & motor controls & pilot devices) - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com