


NOARK

# U41P40550S

SPD UL1449 - 1002764 - 1P - 20kA - 347/600Vac - MCOV 550V - 1NO+1NC remote signal contacts

Surge Protection / Protective Device (SPD) with remote signal contact - UL 1449 - for type 4CA applications - NOARK (U4 series) - L-N / N-PE 20kA (8/20µs) UL nominal discharge current - 1-pole (1P) - 347Vac/600Vac voltage system (UL) rated voltage - MCOV (L-N) 550V maximum continuous operating voltage (Uc MCOV) - 1NO+1NC (1 Normally Open + 1 Normally Closed) signal contact (max. 1.5A at 250Vac / 3A at 125Vac) - DIN rail mounting (17.5mm width) - equivalent to 1002764

## Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

## Specifications

| | |
|---|---|
| **Primary brand** | NOARK |
| **Main function** | Surge arrester / Surge protection device (SPD) |
| **Product series / family name** | Electrical protection > Surge Protection Devices (SPD) > UL1449 |
| **Sub-range name** | U4 series |
| **Network frequency** | 50/60 Hz |
| **Functions** | Surge Protection / Protective Device (SPD) |
| **Design** | remote signal contact<br>for type 4CA applications |
| **Poles** | 1-pole (1P) |
| **Display** | Mechanical indicator -- Green (OK) / Red (FAULT) |
| **Rated voltage (AC)** | 347Vac/600Vac voltage system (UL)<br>2.36kV (L-N) Maximum Limited Voltage (MLV) |
| **Maximum continuous operating voltage (Uc)** | MCOV (L-N) 550V |
| **Cross-section** | for #10AWG...#4AWG / 2.5mm2...25mm2 conductors (solid wire)<br>for #14AWG...#8AWG / 2.5mm2...16mm2 conductors (stranded wire) |
| **Rated discharge current** | L-N / N-PE 20kA (8/20µs) UL nominal discharge current<br>L-N 40kA Imax IEC maximum discharge current |

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

| | |
|---|---|
| **Protection functions** | Protection modes -- L-L / L-N / L-G / N-G<br>Thermal protection |
| **Mounting mode** | DIN rail |
| **Contacts type** | 1NO+1NC (1 Normally Open + 1 Normally Closed) signal contact (max. 1.5A at 250Vac / 3A at 125Vac) |
| **Degree of protection** | IP20 |
| **Dimensions** | H99mm x W17.5mm x D67.5mm<br>H3.9" x W0.69" x D2.66" |
| **Net Width (mm)** | 17.5 mm |
| **Material** | Thermoplastic housing |
| **Ambient air temperature for operation** | -40˚F...+176˚F / -40˚C...+80 ˚C |
| **Order code / Manufacturer SKU** | U41P40550S<br>1002764 |
| **Manufacturer product status** | Commercialized |
| **Equivalent to** | 1002764 |
| **Compliant with standard(s)** | UL 1449<br>CSA C22.2 no.269.5-17<br>CQC compliant<br>CE marking<br>RoHS compliant |
| **Tightening torque** | (power terminals) 18lb.in / 2 N.m |

## Benefits

U4 surge protective devices are suitable for AC 50/60Hz, rated voltage is not more than 600V low-voltage power supply system, used to suppress the transient overvoltage is lower than the equipment impulse overvoltage, discharge the surge energy, so as to protect the system circuit and equipment.

- Indication window of fault status, makes the product more safer to use
- Pluggable module installation, makes maintenance and replacement more convenient
- Signal contact is optional, makes remote indication more flexible

## Documents

NOARK - Surge protective device - U4 series - Datasheet.pdf

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com